

Rittal – The System.

Faster – better – everywhere.

Busbar support – SV 3052.000

Date : Feb 9, 2021

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Busbar support – SV 3052.000

created: 09.02.2021 on www.rittal.com/com-en



Product description

Material:	Fibreglass-reinforced, thermoplastic polyester (PBT) Fire protection corresponding to UL 94-V0
Colour:	RAL 7035
Note on Model No.:	The base component of the busbar support may also be used as a single-pole support.

Product description

To fit busbars:	Type: Busbar E-Cu With dimensions (mm): 50 x 10 With dimensions (mm): 60 x 10 With dimensions (mm): 80 x 10
Number of poles:	3-pole
Centre-to-centre spacing of busbars:	185 mm
Dimensions:	Width: 24 mm Height: 515 mm Depth: 51 mm
Rated current max.:	1600 A
Packs of:	2 pc(s).
Weight/pack:	1.34 kg
Copper weight (kg)	0

per piece):

EAN: 4028177035751

Customs tariff number: 85469010

ETIM 7.0: EC001166

ETIM 6.0: EC001166

eCl@ss 8.0/8.1: 27400607

eCl@ss 6.0/6.1: 27400613

Product description: SV Busbar support, 3-pole, 185 mm bar centre distance, for busbar WH: 50-80x10 mm

Approvals

Approvals: ABS

Certificates: EAC

Declarations: Declaration of conformity