



NT 55/2 Tact² Me I

High performance dust extractor vacuum with Tact² automatic filter clean and stainless steel set-down container



1 Set-down mechanism

- Easy raising and lowering of the container.
- Only the container is removed for emptying. The device and chassis remain at the location of use.

3 Mobile stainless steel container

- The deposited container can be conveniently removed from the chassis and driven for disposal/emptying.

2 Real wet and dry vacuum cleaner

- When vacuuming liquids, the vacuum automatically switches itself off if the maximum filling level is reached, thanks to automatic filling level control.



NT 55/2 Tact² Me I

- Mobile stainless steel container
- Set-down mechanism
- Automatic Filter Cleaning System Tact²

Technical data

Order no.	1.667-237.0	
EAN code	4039784538092	
Current type	Ph / V / Hz	1 / 220 - 240 / 50 - 60
Air flow	l/s	2 x 74
Vacuum	mbar / kPa	254 / 25.4
Container content	l	55
Container material	stainless steel	
Rated input power	W	2760
Standard nominal diameter	DN 40	
Cable length	m	10
Sound pressure level	dB(A)	73
Number of motors	2	
Weight	kg	43
Dimensions (L x W x H)	mm	710 x 570 x 1070

Equipment

Suction hose	m	4 / With bend	Stop swivel castor	■
Suction tube	piece(s) x m	2 x 0.5 / metal		
Wet/dry floor nozzle	mm	360		
Crevice nozzle		■		
Automatic cut-out features at max. filling quality		■		
Antistatic preparation		■		
Stainless steel container		■		
Flat pleated filter		Paper		
Filter cleaning		Tact Filter Clean		
Push handle		■		
Protection class		I		

■ Included in the scope of supply.

NT 55/2 TACT² ME I

1.667-237.0



		Order no.	Anzahl	Dummy	Dummy	Dummy	Price	Description	
Flat pleated filter, paper									
Flat pleated filter, paper	1	6.907-276.0	1 piece(s)					Paper, approved for dust class M.	■
Flat pleated filter HEPA, dust class H									
HEPA flat pleated filter	2	6.904-364.0	1 piece(s)					HEPA flat pleated filter, dust class H (HEPA 13).	□
Flat pleated filter, PTFE									
Flat pleated filter, PTFE	3	6.907-449.0	1 piece(s)					Polyester fleece with PTFE coating, dust class M, for Tact ² vacuum cleaners. Particularly suitable for very adhesive materials.	□

■ Included in the scope of supply.
 □ Available accessories.

NT 55/2 TACT² ME I

1.667-237.0

KÄRCHER


		Order no.	Anzahl	Nennweite	Länge	Breite	Price	Description	
Bend, plastic									
Bend, electroconductive, NW40	1	2.889-172.0	1 piece(s)	DN 40				Bend for the new clip system in nominal size DN 40. Electrically conductive design. Particularly suited to high concentrations of fine dust.	■
Plastic bend	2	5.031-718.0	1 piece(s)	DN 35				Plastic with C 35 clip system.	□
Bend, plastic, electrically conductive	3	5.031-939.0	1 piece(s)	DN 35				Plastic, DN 35 with C 35 clip system, electrically conductive.	□
	4	5.032-427.0	1 piece(s)	DN 40				Plastic, with C 40 clip system, electrically conductive.	□
Floor nozzles									
Wet/dry floor nozzle, plastic Adv, DN 40	5	2.889-153.0	1 piece(s)	40		360 mm		360 mm wide wet and dry floor nozzle with easy-to-change inserts, squeegees.	■
Multi-purpose nozzle, wet/dry	6	6.903-018.0	1 piece(s)	40		370 mm		Aluminium with height-adjustable rollers, brush strips (6.903-064.0) and squeegees (6.903-081.0, oil-resistant).	□
	7	6.906-383.0	1 piece(s)	40		450 mm		Aluminium with height-adjustable rollers, brush strips (6.903-065.0) and squeegees (6.906-146.0).	□
	8	6.906-384.0	1 piece(s)	35		370 mm		Aluminium with height-adjustable rollers, brush strips (6.903-064.0) and squeegees (6.903-081.0, oil-resistant).	□
Wet and dry floor nozzle	9	2.889-117.0	1 piece(s)	40		400 mm		The wet and dry floor nozzle (ID 40) permits a quick squeegee/brush change and is suitable for wet vacuum cleaning of large areas.	□
Wet/Dry floor nozzle standard	10	2.889-173.0	1 piece(s)	35		300 mm		300 mm wide, anthracite-coloured wet/dry floor nozzle, NW 35. With easy-to-change inserts. Including brush strips and squeegees.	□
Wet/Dry floor nozzle standard DN40	11	2.889-174.0	1 piece(s)	40		360 mm		Standard floor nozzle, anthracite-coloured, NW 40, with replaceable brush strips and squeegees. Suitable for all wet and dry applications.	□
Crevice nozzles									
DN 40 crevice nozzle for wet and dry vacuum cleaner	12	5.130-655.0	1 piece(s)	DN 40					■
Crevice nozzle	13	6.900-385.0	1 piece(s)	DN 35	210 mm			Plastic.	□
	14	6.900-922.0	1 piece(s)	35	500 mm			Metal.	□
	15	6.905-817.0	1 piece(s)	40	400 mm				□
Suction tubes, stainless steel									
Set suction tube stainless steel NW40 55	16	2.889-194.0	2 piece(s)	40	550 mm			Stainless steel suction tube set (2 x 0.55 m).	■
Suction tube	17	6.902-081.0	1 piece(s)	40	500 mm			For use in wet or damp environments or for wet vacuuming.	□
	18	6.906-531.0	1 piece(s)	40	1000 mm				□
	19	6.902-154.0	1 piece(s)	35	500 mm			Mainly for wet vacuuming or for vacuuming corrosive media.	□
Bends, stainless steel									
Bend, stainless steel, ID 35	20	6.903-141.0	1 piece(s)	DN 35				Stainless steel.	□
Bend, stainless steel, ID 40	21	6.902-079.0	1 piece(s)	DN 40					□
Bends, metal									
Bend, metal	22	6.900-519.0	1 piece(s)	DN 35				Metal, ID 35.	□
	23	6.900-276.0	1 piece(s)	DN 40				Metal, ID 40.	□
All-purpose brushes									
All-purpose brush	24	6.903-863.0	1 piece(s)	35	120 mm			Natural bristles (ox hair), bristle element 120 x 45 mm, ID 35.	□
Car cleaning nozzles									
DN 40 car nozzle, NT clip system	25	2.840-095.0	1 piece(s)	DN 40		90 mm			□
DN 40 car nozzle	26	6.900-952.0	1 piece(s)	DN 40		90 mm		Plastic.	□

■ Included in the scope of supply. □ Available accessories.

NT 55/2 TACT² ME I

1.667-237.0

KÄRCHER



		Order no.	Anzahl	Nennweite	Länge	Breite	Price	Description	
Rubber suction tools, nose 45°									
Rubber suction tool, nose 45°	27	6.902-104.0	1 piece(s)	35	220 mm			For vacuuming machines, oil-resistant.	☐
	28	6.902-105.0	1 piece(s)	40	220 mm			For vacuuming machinery, oil-resistant.	☐
Pipe dusting nozzles									
Pipe brush 35/100	29	6.903-035.0	1 piece(s)	35				Plastic, tube diameter 100 mm.	☐
Pipe brush 35/200	30	6.903-036.0	1 piece(s)	35				Plastic, tube diameter 200 mm.	☐
Suction tubes, metal									
Suction tube	31	6.900-514.0	1 piece(s)	35	500 mm			Metal, chromium-plated.	☐
Suction tube set, chrome-plated, NW 35 550 mm	32	2.889-191.0	2 piece(s)	35	550 mm			Suction tube set, metal, chrome-plated, NW 35, 2-piece, each 0.55 mm.	☐

■ Included in the scope of supply. □ Available accessories.

NT 55/2 TACT² ME I

1.667-237.0

KÄRCHER


		Order no.	Anzahl	Nennweite	Länge	Price	Description	
Complete suction hoses (clip system)								
Electrically conductive suction hose	1	2.889-141.0	1 piece(s)	DN 40	4 m		4 m long, electrically conductive suction hose with new bayonet and clip fastener.	■
Suction hose	2	4.440-678.0	1 piece(s)	DN 40	4 m		With bend, C ID 40.	□
Suction hose + PFC module, electrically conductive	3	4.440-728.0	1 piece(s)	DN 40	4 m		With bend and module (4.060-533.0), electrically conductive.	□
Electrically conductive suction hose	4	2.889-137.0	1 piece(s)	DN 35	4 m		4 m suction hose with new bayonet and clip fastener. Electrically conductive.	□
Suction hose DN 40, length 4 m	5	2.889-138.0	1 piece(s)	DN 40	4 m		4 m long suction hose with new bayonet and clip fastener.	□
Suction hose	6	2.889-139.0	1 piece(s)	DN 40	2.5 m		Suction hose with new bayonet and clip fastener. Length: 2.5 m.	□
Suction hose, oil-resistant	7	2.889-140.0	1 piece(s)	DN 40	4 m		Oil-resistant suction hose with new bayonet and clip fastener. Length: 4 m.	□
Electrically conductive suction hose	8	2.889-142.0	1 piece(s)	DN 40	2.5 m		Suction hose, electrically conductive, with new bayonet and clip fastener. 2.5 m long.	□
Suction hose	9	2.889-161.0	1 piece(s)	DN 35	2 m		2 m long suction hose with new clip fastening, DN 35. Ideal for Kärcher dry vacuum cleaners. Robust, flexible and durable.	□
Repair kits								
Repair kit, C 40	10	2.639-873.0	1 piece(s)	40			Suction hose repair kit (clip system).	□
Repair kit, ID 61	11	2.862-038.0	1 piece(s)	61			Suction hose repair kit.	□
Suction hoses (clip system)								
Suction hose	12	6.906-279.0	1 piece(s)	DN 40	10 m		With bayonet and clip connection, C-45.	□
	13	6.906-321.0	1 piece(s)	40	4 m		With bayonet and clip connection, C 40.	□
	14	6.906-714.0	1 piece(s)	DN 40	4 m		With bayonet and clip connection, oil-resistant, C-45.	□
	15	6.906-546.0	1 piece(s)	DN 40	4 m		With bayonet and clip connection, electrically conductive, C 40.	□
	16	6.906-635.0	1 piece(s)	DN 40	16 m		With bayonet and clip connection, C-40.	□
	17	6.906-877.0	1 piece(s)	DN 40	10 m		With bayonet and clip connection, electrically conductive, C-40.	□
Suction hoses complete								
Suction hose, complete	18	4.440-264.0	1 piece(s)	DN 61	4 m		Plastic.	□
	19	4.440-328.0	1 piece(s)	DN 61	3 m		Industrial hose, PVC / elastomer with steel spiral, smooth inside.	□
	20	4.440-467.0	1 piece(s)	DN 61	10 m		Plastic.	□
Suction hose, complete, oil-resistant	21	4.440-613.0	1 piece(s)	DN 61	4 m		Oil-resistant.	□
Suction hose, complete, electrically conductive	22	4.440-616.0	1 piece(s)	DN 61	4 m		Electrically conductive.	□
Suction hose, complete	23	4.440-263.0	1 piece(s)	DN 40	4 m		Plastic.	□
	24	4.440-303.0	1 piece(s)	DN 40	4 m		Oil-resistant.	□
	25	4.440-463.0	1 piece(s)	DN 40	10 m		Plastic.	□
	26	4.440-466.0	1 piece(s)	DN 40	10 m		Electrically conductive, plastic.	□
Suction hose, complete, oil-resistant	27	4.440-612.0	1 piece(s)	DN 40	10 m		Oil-resistant.	□
Connecting sleeves								
Adapter, ID 32/35, with internal thread	28	6.902-077.0	1 piece(s)	DN 32			For connecting two suction hoses (not ESB 28 and 34).	□

■ Included in the scope of supply. □ Available accessories.

NT 55/2 TACT² ME I

1.667-237.0



		Order no.	Anzahl	Nennweite	Länge		Price	Description	
Connecting adapter, ID 40, with internal thread	29	6.900-286.0	1 piece(s)	DN 40				For connecting two suction hoses, threaded at both ends.	☐
Connecting sleeve, ID 61, with female thread	30	6.902-078.0	1 piece(s)	DN 61					☐
Extension hoses (clip system)									
Extension hose	31	6.906-237.0	1 piece(s)	DN 32	2.5 m			For all C-32 and C-35 hoses.	☐
	32	6.906-344.0	1 piece(s)	DN 40	2.5 m			For all C-40 hoses.	☐
	33	2.889-146.0	1 piece(s)	DN 40	2.5 m			Extension hose for new clip system ID 40. Length: 2.5 m.	☐

■ Included in the scope of supply. □ Available accessories.

NT 55/2 TACT² ME I

1.667-237.0

KÄRCHER



		Order no.	Flow rate	Inlet temperature	Length	Length	Price	Description	
Teleskopstangen									
Telescopic lance TL 10 H	1	4.762-611.0		max. 60 °C				Up to 10 m reach: hybrid telescopic lance TL 10 H. Comprising carbon-glass fibre mix and suitable for multifunctional use. Simple retraction and extension thanks to quick-release fasteners.	☐
Telescopic lance TL 10 C	2	4.762-612.0		max. 60 °C				Carbon fibre telescopic lance TL 10 C. With up to 10 m reach and practical quick-release fasteners. Multifunctional use for cleaning facades, windows or solar panels.	☐
TL vacuum cleaner adapter	3	9.751-306.0						TL suction cup for 10 and 14 m long telescopic lances comprising suction bend connection (DN 35, DN 40) and connection for the suction nozzles.	☐

■ Included in the scope of supply. □ Available accessories.

NT 55/2 TACT² ME I

1.667-237.0

KÄRCHER


		Order no.	Anzahl	Nennweite		Price	Description	
Y-adapter kit								
Y-adapter kit	1	2.637-217.0	1 piece(s)	35			Distributor, plastic.	☐
Connection adapter C ID (clip to cone), electrically conductive								
Connection adapter C DN 35	2	5.407-112.0	1 piece(s)	35			C 35 hose connection for ID 35 accessories, electrically conductive.	☐
Connection adapter C DN 40	3	5.407-109.0	1 piece(s)	C-DN 40			C 40 hose connection for ID 35 accessories, electrically conductive.	☐
	4	5.407-111.0	1 piece(s)	40			C 40 hose connection for ID 40 accessories, electrically conductive.	☐
Adapter clip DN 35 on cone DN 35	5	5.407-005.0						☐
Adapter clip DN 40 to cone DN 40	6	5.407-006.0		DN 40				☐
Connection adapter for power tools, clip-on, electrically conductive								
Connection adapter for power tools, C 35, electrically conductive	7	5.453-042.0	1 piece(s)	35			Plastic, adjustable from ID 26-36 (Te / Eco M / H), electrically conductive.	☐
	8	5.453-048.0	1 piece(s)	35			Inside Ø 25.4 mm, outside Ø 34.6 mm / 38 mm, electrically conductive.	☐
	9	5.453-050.0	1 piece(s)	35			Inside Ø 27 mm, outside Ø 36.5 mm / 38.8 mm, electrically conductive.	☐
Adapter for electric power tools, screwable								
Adapter for electric power tools, screwable, ID 35	10	5.453-016.0	1 piece(s)	35			Plastic, adjustable from ID 26-36.	☐
	11	5.453-026.0	1 piece(s)	35			Inside Ø 28.6 mm, outside Ø 37.3 mm / 38.8 mm.	☐
	12	6.902-059.0	1 piece(s)	35			Inside Ø 32 mm, outside Ø 39 mm.	☐
	13	6.902-095.0	1 piece(s)	35			Inside Ø 28 mm, outside Ø 34 / 38.8 mm, electrically conductive.	☐
Expansion pieces (tube -> nozzle)								
Adapter	14	5.453-019.0	1 piece(s)	40			From ID 40 to ID 61, plastic.	☐
Reducing sleeves								
Reducer	15	5.407-108.0	1 piece(s)	40			From C 40 hose with outer thread 35 for connection bushing, screwable, ID 35.	☐
Reduction bushing	16	5.407-113.0	1 piece(s)	40			Reduction bushing from clip C 40 to clip C 35.	☐
Reducers (tube -> nozzle)								
Reducer	17	6.902-017.0	1 piece(s)	40			From ID 40 to ID 35, plastic.	☐
Reducer from ID 35 to ID 32	18	6.902-072.0	1 piece(s)	35			From ID 35 to ID 32, metal.	☐
Reduction/expansion adapter kit								
Set of reducers / adapter sleeves	19	2.860-117.0	1 piece(s)				ID 40/35, ID 35/32 (tube -> nozzle), plastic.	☐

■ Included in the scope of supply. □ Available accessories.

NT 55/2 TACT² ME I
1.667-237.0



		Order no.	ID				Price	Description	
Target-group-specific accessory kits for vacuum cleaners									
Professional cleaning kit	1	2.637-353.0	DN 40					Professional cleaning kit.	☐
Swarf kit	2	2.640-760.0	DN 61					Swarf kit.	☐

■ Included in the scope of supply. □ Available accessories.

NT 55/2 TACT² ME I
1.667-237.0



		Order no.	Anzahl	Breite			Price	Description	
Other									
CS 40 Me	1	2.863-026.0	1 piece(s)					Cyclone preseparator for use with wet and dry vacuum cleaners for very large quantities of dust.	☐
Adapter connection, electroconductive	2	5.031-436.0							☐

■ Included in the scope of supply. □ Available accessories.

NT 55/2 TACT² ME I
1.667-237.0



		Order no.	Length	Colour	Quantity	Price	Description	
Miscellaneous								
Extension cable	1	6.647-022.0	20 m		1 piece(s)		Extension cable, 20 m, 3x1.5 mm ² . With splash-proof earthing pin plug, strain relief and anti-kink sleeve.	☐

■ Included in the scope of supply. ☐ Available accessories.

NT 55/2 TACT² ME I
1.667-237.0



		Order no.	Quantity	ID	Length / width		Price	Description	
Emptying bags									
Disposal bag PE Ø 510 mm 100 l	1	6.904-348.0	20 piece(s)					For safe, dust-free emptying.	☐

■ Included in the scope of supply. □ Available accessories.