

Delock Antenna Cable N plug > RP-SMA plug CFD400 LLC400 1 m low loss

Description

This high-quality coaxial cable ensures a reliable connection of components of the radio frequency technology. It is characterised by a very low attenuation.



Specification

- Connector: N plug > RP-SMA plug
- Cable type: CFD400, LLC400
- Impedance: 50 Ohm
- Cable Attenuation:
2.4 GHz: ca. 0.22 dB per meter
5.7 GHz: ca. 0.35 dB per meter
- Diameter: ca. 10.5 mm
- Smallest bending radius: 51.5 mm
- Colour: black
- Cable length: ca. 1 m

System requirements

- Device with a free RP-SMA connector

Package content

- Antenna cable

Item No. 13019

EAN: 4043619130191

Country of origin: Taiwan, Republic of China

Package: Box

Images





Interface	
Connection 1:	N plug
Connection 2:	RP-SMA plug
Technical characteristics	
Impedance:	50 Ohm
Physical characteristics	
Cable attenuation:	2.4 GHz: ca. 0.22 dB per meter
	5.7 GHz: ca. 0.35 dB per meter
Cable diameter:	10.5 mm
Cable colour:	black
Cable length:	1 m
Cable type:	CFD400, LLC400
Smallest bending radius:	51.5 mm