

JUST INTEGRATE, AND
SWITCH TWO LIGHTS
THE SMART WAY

Switch actuator for brand switches – 2 channels

HmIP-BS2

The Homematic IP Switch Actuator makes controlling lights via two channels smart. The flush-mounted solution can be flexibly retrofitted. That allows you to simply continue using your preferred switch designs. The lights can then be conveniently controlled via your smartphone, fully-automatically via a time profile or in the usual way with buttons.



homematic 
Smart living, simply comfortable

INTELLIGENT LIGHT SWITCHING

Up to two connected lights can be conveniently switched on and off via independent channels for the ideal lighting mood in your smart home.

The top button switches Channel 1 on or off, while the bottom button controls the second channel.

TECHNICAL SPECIFICATIONS

Supply voltage	230 V/50 Hz
Current consumption	6 A max.
Power consumption in standby	0.2 W
Maximum switching capacity	1380 W
Load type	Ohmic load
Relay	2x NO,1-pole, monostable
Cable type and cross section	rigid and flexible cable, 0.75 - 1.5 mm ²
Installation	only in normal commercial switch boxes (device boxes) in accordance with DIN 49073-1 Recommended device box >50 mm
Degree of protection	IP20
Ambient temperature	5 to 35 °C
Dimensions (W x H x D)	71 x 71 x 37 mm
Weight	59 g
Radio frequency band	868.0-868.6 MHz 869.4-869.65 MHz
Typical range in open space	150 m

LOGISTICS DATA

Product reference	156757A0
EAN code	4047976567577
Short description	HmIP-BS2
Packing unit	90
Packing dimensions	122 x 112 x 48 mm
Weight incl. packaging	139.1 g

PACKAGE CONTENTS

Homematic IP switch actuator for brand switches – 2 channels	
Screws 3.2 x 15 mm (2x)	
Screws 3.2 x 25 mm (2x)	
Operating manual	