

## DS-2CE16D0T-LFS

### 2 MP Dual Light Audio Fixed Mini Bullet Camera



- High quality imaging with 2 MP, 1920×1080 resolution
- 2.8 mm, 3.6 mm fixed focal lens
- Up to 30 m IR distance for bright night imaging
- Up to 20 m white light distance for bright night imaging
- One port for four switchable signals (TVI/AHD/CVI/CVBS)
- High quality audio with audio over coaxial cable, built-in mic
- Water and dust resistant (IP67)






## ▪ Specification

| Camera                   |                                                                                                                                          |
|--------------------------|------------------------------------------------------------------------------------------------------------------------------------------|
| Image Sensor             | 2 MP CMOS                                                                                                                                |
| Max. Resolution          | 1920 (H) × 1080 (V)                                                                                                                      |
| Min. Illumination        | 0.01 Lux @ (F1.2, AGC ON), 0 Lux with IR                                                                                                 |
| Shutter Time             | PAL: 1/25 s to 1/50, 000 s; NTSC: 1/30 s to 1/50, 000 s                                                                                  |
| Day & Night              | ICR                                                                                                                                      |
| Angle Adjustment         | Pan: 0 to 360°, Tilt: 0 to 180°, Rotation: 0 to 360°                                                                                     |
| Signal System            | PAL/NTSC                                                                                                                                 |
| Lens                     |                                                                                                                                          |
| Lens Type                | 2.8 mm, 3.6 mm fixed focal lens                                                                                                          |
| Focal Length & FOV       | 2.8 mm, horizontal FOV: 101°, vertical FOV: 56°, diagonal FOV: 118°<br>3.6 mm, horizontal FOV: 78°, vertical FOV: 42°, diagonal FOV: 92° |
| Lens Mount               | M12                                                                                                                                      |
| Illuminator              |                                                                                                                                          |
| Supplement Light Type    | White Light, IR                                                                                                                          |
| Supplement Light Range   | IR : Up to 30 m<br>White Light : Up to 20 m                                                                                              |
| Image                    |                                                                                                                                          |
| Image Settings           | Brightness, Sharpness, Smart IR                                                                                                          |
| Frame Rate               | TVI: 1080P @ 30 fps, 1080P @ 25 fps<br>AHD: 1080P @ 30 fps, 1080P @ 25 fps<br>CVI: 1080P @ 30 fps, 1080P @ 25 fps<br>CVBS: PAL/NTSC      |
| Day/Night Mode           | IR/White Light                                                                                                                           |
| Wide Dynamic Range (WDR) | Digital WDR                                                                                                                              |
| Image Enhancement        | Yes                                                                                                                                      |
| White Balance            | Auto/Manual                                                                                                                              |
| AGC                      | Yes                                                                                                                                      |
| Interface                |                                                                                                                                          |
| Video Output             | Switchable TVI/AHD/CVI/CVBS                                                                                                              |
| General                  |                                                                                                                                          |
| Material                 | Metal                                                                                                                                    |
| Dimension                | 138.8 mm × 60.9 mm × 57.9 mm (5.47" × 2.4" × 2.3")                                                                                       |
| Weight                   | Approx. 266 g (0.59 lb.)                                                                                                                 |
| Operating Condition      | -40 °C to 60 °C (-40 °F to 140 °F), humidity: 90% or less (non-condensation)                                                             |
| Communication            | HIKVISION-C                                                                                                                              |
| Language                 | English                                                                                                                                  |
| Power Supply             | 12 VDC ± 25%<br><i>*You are recommended to use one power adapter to supply the power for one camera.</i>                                 |
| Consumption              | Max. 3.3 W                                                                                                                               |
| Approval                 |                                                                                                                                          |
| Protection               | IP67                                                                                                                                     |

## ▪ Available Model

DS-2CE16D0T-LFS

## ▪ Dimension




## ▪ Accessory

### ▪ Optional

**DS-1280ZJ-XS**

**Junction box**



Distributed by



## HIKVISION®

### Headquarters

No.555 Qianmo Road, Binjiang District,  
Hangzhou 310051, China  
T +86-571-8807-5998  
overseasbusiness@hikvision.com

**Hikvision USA**  
T +1-909-895-0400  
sales.usa@hikvision.com

**Hikvision Australia**  
T +61-2-8589-4233  
salesau@hikvision.com

**Hikvision India**  
T +91-22-28469900  
sales@pramahikvision.com

**Hikvision Canada**  
T +1-866-200-6690  
sales.canada@hikvision.com

**Hikvision Thailand**  
T +662-275-9949  
sales.thailand@hikvision.com

**Hikvision Europe**  
T +31-23-5542770  
sales.eu@hikvision.com

**Hikvision Italy**  
T +39-0438-6902  
info.it@hikvision.com

**Hikvision Brazil**  
T +55 11 3318-0050  
Latam.support@hikvision.com

**Hikvision Turkey**  
T +90 (216)521 7070- 7074  
sales.tr@hikvision.com

**Hikvision Malaysia**  
T +601-7652-2413  
sales.my@hikvision.com

**Hikvision UK & Ireland**  
T +01628-902140  
sales.uk@hikvision.com

**Hikvision South Africa**  
Tel: +27 (10) 0351172  
sale.africa@hikvision.com

**Hikvision France**  
T +33(0)1-85-330-450  
info.fr@hikvision.com

**Hikvision Kazakhstan**  
T +7-727-9730667  
nikia.panfilov@hikvision.ru

**Hikvision Vietnam**  
T +84-974270888  
sales.vt@hikvision.com

**Hikvision UAE**  
T +971-4-4432090  
salesme@hikvision.com

**Hikvision Singapore**  
T +65-6684-4718  
sg@hikvision.com

**Hikvision Spain**  
T +34-91-737-16-55  
info.es@hikvision.com

**Hikvision Tashkent**  
T +99-87-1238-9438  
uzb@hikvision.ru

**Hikvision Hong Kong**  
T +852-2151-1761  
info.hk@hikvision.com

**Hikvision Russia**  
T +7-495-669-67-99  
saleru@hikvision.com

**Hikvision Korea**  
T +82-(0)31-731-8817  
sales.korea@hikvision.com

**Hikvision Poland**  
T +48-22-460-01-50  
info.pl@hikvision.com

**Hikvision Indonesia**  
T +62-21-2933759  
Sales.Indonesia@hikvision.com

**Hikvision Colombia**  
sales.colombia@hikvision.com