

AXIS Q1656-BLE Box Camera

Outdoor barebone model in 4 MP with IR

With 4 MP resolution at up to 60 fps, a 1/1.8" sensor, and Lightfinder 2.0, AXIS Q1656-BLE delivers exceptional video quality even in poor light conditions. Based on the latest Axis system-on-chip (SoC), it offers support for advanced features and applications based on deep learning on the edge. And AXIS Object Analytics provides highly nuanced object classification. With built-in cybersecurity features, it prevents unauthorized access and safeguards your system. This outdoor-ready barebone unit comes without lens and mounting for maximum flexibility. Furthermore, with selectable IR wavelength, you can choose between covert or semi-covert LED illumination to meet your needs.

- > **Exceptional images with 1/1.8" sensor**
- > **Support for analytics with deep learning**
- > **Built-in cybersecurity features**
- > **Ready to customize for specific needs**
- > **Built-in wiper for snow and rain**



AXIS Q1656-BLE Box Camera

Camera		Onscreen controls	Electronic image stabilization				
Image sensor	1/1.8" progressive scan RGB CMOS		Day/night shift				
Day and night	Automatically removable infrared-cut filter		Defogging				
Minimum illumination	4 MP 25/30 fps with Forensic WDR and Lightfinder 2.0 Color: 0.05 lux at 50 IRE, F1.5 B/W: 0.01 lux at 50 IRE, F1.5 4 MP 50/60 fps with Lightfinder 2.0 Color: 0.1 lux at 50 IRE, F1.5 B/W: 0.02 lux at 50 IRE, F1.5 Lens not included 0 lux with IR illumination on		Wide dynamic range Video streaming indicator IR illumination Timed wiper Wiper Heater				
Shutter speed	1/47500 s to 1 s	Event conditions	Analytics, external input, supervised external input, edge storage events, virtual inputs through API Audio: audio detection Device status: above operating temperature, above or below operating temperature, below operating temperature, IP address removed, network lost, new IP address, shock detected, storage failure, system ready, within operating temperature, casing open Video: tampering, average bitrate degradation, day-night mode Edge storage: recording ongoing, storage disruption I/O: digital input, manual trigger, virtual input PTZ: PTZ malfunctioning, PTZ movement, PTZ preset position reached, PTZ ready Scheduled and recurring: scheduled event Video: live stream open				
System on chip (SoC)			Event actions	Overlay text, external output activation, play audio clip, zoom preset I/O: toggle I/O once, toggle I/O while the rule is active Illumination: use lights, use lights while the rule is active MQTT: publish Notification: HTTP, HTTPS, TCP, and email Pre- and post-alarm video or image buffering for recording or upload PTZ: PTZ preset, start/stop guard tour Record video: SD card and network share SNMP traps: send, send while the rule is active Upload of images or video clips: FTP, SFTP, HTTP, HTTPS, network share, and email			
Model	ARTPEC-8			Data streaming	Event data		
Memory	2048 MB RAM, 8194 MB Flash				Built-in installation aids	Remote back focus, leveling assistant, pixel counter i-CS lens: Remote zoom and focus	
Compute capabilities	Deep learning processing unit (DLPU)				Analytics		
Video					AXIS Object Analytics	Object classes: humans, vehicles (types: cars, buses, trucks, bikes) Trigger conditions: line crossing, object in area Up to 10 scenarios Metadata visualized with color-coded bounding boxes Polygon include/exclude areas Perspective configuration ONVIF Motion Alarm event	
Video compression	H.264 (MPEG-4 Part 10/AVC) Baseline, Main and High Profiles H.265 (MPEG-H Part 2/HEVC) Main Profile Motion JPEG		Applications	Included AXIS Object Analytics AXIS Video Motion Detection Supported Support for AXIS Camera Application Platform enabling installation of third-party applications, see axis.com/acap			
Resolution	16:9 2688x1512 Quad HD to 160x90 4:3 2016x1512 to 160x120			General		Casing IP66-, IP67-, and NEMA 4X-rated, IK10 impact-resistant aluminum enclosure with integrated dehumidifying membrane IK08 impact-resistant glass front window with wiper weathershield with black anti-glare coating Color: white NCS S 1002-B For repainting instructions, go to the product's support page. For information about the impact on warranty, go to axis.com/warranty-implication-when-repainting .	
Frame rate	No WDR: Up to 60/50 fps (60/50 Hz) in all resolutions WDR: Up to 30/25 fps (60/50 Hz) in all resolutions						Sustainability
Video streaming	Multiple, individually configurable streams in H.264, H.265 and Motion JPEG Axis Zipstream technology in H.264 and H.265 Controllable frame rate and bandwidth VBR/ABR/MBR H.264/H.265 Video streaming indicator				Connectors		
Multi-view streaming	Up to 8 individually cropped out view areas	Application Programming Interface	Open API for software integration, including VAPIX® and AXIS Camera Application Platform; specifications at axis.com One-click cloud connection ONVIF® Profile G, ONVIF® Profile M, ONVIF® Profile S, and ONVIF® Profile T, specification at onvif.org				
Image settings	Saturation, contrast, brightness, Forensic WDR: Up to 120 dB depending on scene, white balance, day/night threshold, tone mapping, exposure mode, exposure zones, defogging, barrel distortion correction, electronic image stabilization, compression, rotation: 0°, 90°, 180°, 270° including Corridor Format, mirroring, dynamic text and image overlay, polygon privacy mask			System integration			
Pan/Tilt/Zoom	Digital PTZ, 2.5x optical zoom, preset positions Uploadable PTZ driver (Pelco D pre-installed)						
Audio							
Audio streaming	Two-way, full duplex Noise reduction						
Audio encoding	24bit LPCM, AAC-LC 8/16/32/48 kHz, G.711 PCM 8 kHz, G.726 ADPCM 8 kHz, Opus 8/16/48 kHz Configurable bit rate						
Audio input/output	External microphone input or line input, line output, ring power, digital audio input, automatic gain control						
Network							
Security	Password protection, IP address filtering, HTTPS ^a encryption, IEEE 802.1x (EAP-TLS) ^a network access control, digest authentication, user access log, centralized certificate management, brute force delay protection, signed firmware, secure boot, Axis Edge Vault, Axis device ID, secure keystore (CC EAL4 certified), TPM (FIPS 140-2 certified)						
Network protocols	IPv4, IPv6 USGv6, HTTP, HTTPS ^a , HTTP/2, TLS ^a , QoS Layer 3 DiffServ, FTP, SFTP, CIFS/SMB, SMTP, Bonjour, UPnP®, SNMP v1/v2c/v3 (MIB-II), DNS, DynDNS, NTP, RTSP, RTP, SRTP, TCP, UDP, IGMPv1/v2/v3, RTCP, ICMP, DHCPv4/v6, ARP, SSH, LLDP, MQTT v3.1.1, Syslog						
System integration							
Application Programming Interface							

	DC input, terminal block, 3.5 mm mic/line in, 3.5 mm line out i-CS connector (compatible with P-Iris and DC-iris)
IR illumination	OptimizedIR with power-efficient, long-life 850 nm IR LEDs Range of reach 50 m (164 ft) or more depending on the scene
Illumination LED	Power-efficient, long-life white LED Range of reach 25 m (82 ft) or more depending on the scene
Storage	Support for microSD/microSDHC/microSDXC card Support for SD card encryption (AES-XTS-Plain64 256bit) Recording to network-attached storage (NAS) For SD card and NAS recommendations see axis.com
Operating conditions	-40 °C to 60 °C (-40 °F to 140 °F) Arctic Temperature Control: Start-up at -40 °C (-40 °F) Maximum temperature according to NEMA TS 2 (2.2.7): 74 °C (165 °F) Humidity 10–100% RH (condensing)
Storage conditions	-40 °C to 65 °C (-40 °F to 149 °F) Humidity 5–95% RH (non-condensing)
Approvals	EMC CISPR 24, CISPR 35, EN 55032 Class A, EN 55035, EN 61000-3-2, EN 61000-3-3, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class A, ICES-3(A)/NMB-3(A), EN 50121-4, IEC 62236-4, KS C 9832 Class A, KS C 9815, KS C 9835, KS C 9547, RCM AS/NZS CISPR 32 Class A, VCCI Class A Safety IEC/EN/UL 62368-1, IEC/EN/UL 60950-22, IEC 62471, IS 13252 Environment Environment IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-6, IEC 60068-2-14, IEC 60068-2-27, IEC 60068-2-78, IEC/EN 60529 IP66/IP67,

IEC/EN 62262 IK10, NEMA 250 Type 4X, NEMA TS 2 (2.2.7-2.2.9), ISO 21207 (Method B)

Network
NIST SP500-267

Dimensions	404 x 159 x 182 mm (16 x 6.3 x 7.2 in)
Weight	4.1 kg (9.0 lb)
Included accessories	Sunshield, connector kit, resistorx® T20 tool, installation guide, Windows® decoder 1-user license
Optional accessories	AXIS T8415 Wireless Installation Tool AXIS Surveillance Cards For more accessories, see axis.com
Optional lenses	Lens CS 4–10 mm F0.9 P-Iris Lens i-CS 9–50 mm F1.5 8 MP Lens CS 12–50 mm F1.4 P-Iris 8 MP Lens i-CS 1/1.8" 3.9–10 mm F1.5
Video management software	AXIS Companion, AXIS Camera Station, video management software from Axis Application Development Partners available at axis.com/vms
Languages	English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Polish, Traditional Chinese
Warranty	5-year warranty, see axis.com/warranty

a. This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. ([openssl.org](https://www.openssl.org)), and cryptographic software written by Eric Young (eyay@cryptsoft.com).

Environmental responsibility:

[axis.com/environmental-responsibility](https://www.axis.com/environmental-responsibility)