

TA-UC-2A4C-PD75-01-BK

6-port 75W GaN USB fast charger, black

- A total of 75 W charging power for your smartphones or tablets
- Type-C port or standard USB port for fast charging most smartphones
- Supports both USB PD and QC 3.0 fast charging protocol
- GaN technology enables a more compact energy efficient design



Features

- 6-port 75 W USB fast charger: supports both QC 3.0 and PowerDelivery (PD) specification
- GaN technology: compact design and increased energy efficiency
- Type-C ports support 25 W PD, Type-A ports supports 18W QC 3.0
- Intelligent over-current, over-voltage, short circuit and overheat protection
- Includes practical desktop stand and power cord

Packaging

Q'ty in crtn, pcs	48
Crtn volume, CUM	0.07
Crtn weight, kgs	20.58
Individual package size LxWxH:	40x145x170 mm
Carton size LxWxH:	510x390x350 mm
Country of origin	CN
Barcode	8716309133876
Customs code	8504408390

Certificates



Specifications

Input voltage: 100-240 V~ 50/60 Hz, 2.0 A
Output ports: 3x USB Type-C, 1x USB-Type-A
USB-C1/C2/C3/C4: 5.0V / 3A, 9.0V / 2.77A, 12V / 2.08A (Max. 25W)

USB-A1/A2: 5.0V / 3.0A, 9.0V / 2.0A, 12.0V / 1.5A (Max. 18W)

USB-C1+C4: 5.0V / 3.0A (Max. 15W)

USB-C2+A1: 5.0V / 3.0A (Max. 15W)

USB-C3+A2: 5.0V / 3.0A (Max. 15W)

C1/C4+C2+C3: 25W+25W+25W (Max. 75W)

USB-(C1+C4)+(C2+A1)+(C3+A2)= 5.0V / 3.0A+5.0V / 3.0A+5.0V / 3.0A (Max. 45W)

Standby power consumption: <0.1 W

Average efficiency: >86 %

Efficiency at 25% load: >87 %

Efficiency at 100% load: >85.6 %

Output protection: short circuit, over-voltage, overcharge, overheat

Power cord length: 1.5 m

Dimensions: 80 mm x 60mm x 85 mm

Net weight: 247 g

System requirements

The fast charging function is only available for devices that support fast charging