

XM7 Series

Mobile Label Printers



Logistics

Field
Service

Retail



Healthcare

Powerful and Rugged



XM7-20



XM7-40



XM7-20

XM7-40

Ultimate Printing Capability

- Fully compatible with SLCS, BPL-Z™, BPL-C™ and BXL / POS : Interchanged without setting the mode
- Fast Liner & Linerless label printing
- Smart Media Detection™
- Anywhere Anyfont™ (Unicode)
- Direct printing from the SAP® Smart Forms
- BIXOLON Profile Manager XPM™, XCM™



Exceptional Mobility

- Smart battery providing visibility over status and life cycle
- Simultaneously connects both Bluetooth 5.0 (MFi certified) and Dual-band WLAN (2.4GHz and 5GHz)
- Supporting all major operating systems
- Easy Bluetooth Pairing™
- SoftAP : Simple Wi-Fi set up to a mobile device
- Smart Connection™ – Switching from SoftAP to Infrastructure mode



Compact and Rugged Design

- Built with a large colour display for easy set-up and battery status management
- Embedded peeler and media holder
- Up to 2.1 m / 7 ft. drop rate (XM7-20)
- IP54 water and dust proof
- Enabling USB C-type charging

BIXOLON
a Better Solution for your Business™

XM7 Series

Mobile Label Printers



Specifications

Reported by
Chunichisha



Printer Specifications

Print Method

Direct Thermal

Print Speed

XM7-40: Up to 5 ips
(127 mm/sec - Liner, Linerless)

XM7-20: Up to 6 ips
(152 mm/sec - Liner, Linerless)

Print Resolution

203 dpi

Print Width

XM7-40: Up to 104 mm

XM7-20: Up to 48 mm

Sensing

Paper End

Gap

Black Mark

Paper Cover Open

Peel-off

Media Characteristics

Media Type

XM7-40: Liner, Linerless (Optional)

XM7-20: Liner, Linerless (Optional), Notch, Receipt

Media Width

XM7-40: 50 ~ 112 mm (1.97 ~ 4.41 inch)

XM7-20: 25 ~ 58 mm (1.0 ~ 2.28 inch)

Media Roll Diameter

XM7-40: Up to 66mm

XM7-20: Up to 57mm

Media Thickness

XM7-40: 0.07 ~ 0.15mm

XM7-20: 0.07 ~ 0.19mm

Media Inner Core

19mm, 12mm

Supply Method

Easy Paper Loading

Physical Characteristics

Dimensions (W x L x H)

XM7-40: 158 x 186 x 82 mm
(6.23 x 7.33 x 3.23 inch)

XM7-20: 92.9 x 168.2 x 69.2 mm
(3.66 x 6.62 x 2.72 inch)

Weight

XM7-40

Including battery: approx. 1,090 g (2.41 lbs)

Paper : approx. 360 g (0.79 lbs)

XM7-20

Including battery: 600g (1.32 lbs.)

Paper : 120g (0.26 lbs.)

Physical Characteristics

Electrical

USB Type-C Power delivery charging support,
EnergyStar Certified

XM7-40

7.2 V Li-ion, 6800 mAh (Nominal) Smart Battery,
Rechargeable

XM7-20

Standard: 7.3 V Li-ion, 2850 mAh (Nominal),
Rechargeable

Optional: 7.2 V Li-ion 3400 mAh (Nominal) Smart
Battery, Rechargeable

Peeler

Supported

Media Holder

Yes (Inner core: 19mm)

Display

TFT LCD (IPS, 240 x 320 pixels)

Performance Characteristics

Memory

128 MB SDRAM, 256 MB Flash

256 MB SDRAM, 512 MB Flash (Optional)

Interface

Standard: USB V2.0 HS + Serial

Optional: USB V2.0 HS + Serial + Bluetooth /
WLAN / Dual (Bluetooth + WLAN)

Bluetooth: V5.0 (MFi certified)

WLAN: 802.11a/b/g/n (Infrastructure, Ad-hoc, Wi-Fi Direct, SoftAP) - WEP40/104, WPA1/2 (PSK, EAP)

Easy Bluetooth Pairing™ via NFC

Environment Characteristics

Temperature

Operating: -15 ~ 50°C (5 ~ 122°F)

Storage: -30 ~ 70°C (-22 ~ 158°F)

Humidity

Operating: 10 ~ 80% RH

Sealing

IP54

Drop Rate

XM7-40: 1.8 m (6 ft.)

XM7-20: 2.1 m (7 ft.)

Software

Emulation

SLCS, BPL-Z™, BPL-CT™, BXL / POS

Driver / Utility

Windows Driver (Europlus / Seagull),
Linux / Mac CUPS Driver, Virtual COM USB Driver,
Utility Program, LabelArtist-II™, Bartender UL,
OPOS / JPOS Driver, SAP® Device Driver

SDK / Plugin

Android / iOS / Windows SDK, Linux SDK,
Chrome SDK, Xamarin SDK, Cordova Plugin

Application

Label Artist™ Mobile (Android, iOS),
mPrint App (Android, iOS),
mPrint Server (Windows, Android, iOS)

MDM (Optional)

BIXOLON Profile Manager

- XPM™, XCM™ (Windows, Android)

Fonts / Graphics / Symbolologies

Fonts

10 SLCS / One SLCS / 16 BPL-Z™ / One BPL-Z™ /
7 BPL-CT™ / 23 Code Page /

Unicode supported (UTF-8, UTF-16LE, UTF-16BE)

Graphics

Supporting user-defined fonts, graphics,
formats, layouts and logos

Barcode Symbolologies

1D: Codabar, Code 11, Code 39, Code 93,
Code 128, EAN-13, EAN-8, Industrial 2-of-5,
Interleaved 2-of-5, Logmars, MSI, Plessey,
Postnet, GS1 DataBar (RSS-14),
Standard 2-of-5, UPC / EAN extensions,
UPC-A, UPC-E, IMB

2D: Aztec, Codablock, Code 49, Data Matrix,
MaxiCode, MicroPDF417, PDF417, QR code,
TLC 39

Accessories

Standard

XM7-40: Belt Strap, Smart Battery, SMPS,
Power Cord,
Media Disk (Inner core : 12mm)

XM7-20: Belt Strap, Battery Pack, SMPS,
Power Cord,
Media Disk (Inner core : 12mm)

Optional

Shoulder Strap, Single Battery Charger,
Quad Battery Charger, Serial / USB Cable,
Fixed Serial / USB Cable,
Vehicle Charger (XM7-20 only),
Smart Battery(XM7-20 only)

Supplies

B-linerless™ : BIXOLON's flexible and ecological
linerless label consumables

BR_XM7 Series_EN_JAN21_V1

Copyright © BIXOLON Co., Ltd. All rights reserved. Features and specifications are subject to change without prior notice.

BIXOLON
www.BIXOLON.com

BIXOLON Co.,Ltd.
+82 31 218 5500
sales@bixolon.com

BIXOLON America Inc.
+1 858 764 4580
sales@bixolonusa.com

BIXOLON Europe GmbH
+49 211 68 78 54 0
sales@bixolon.de

BIXOLON MEA
+971 50 974 9698
russell@bixolon.com