

# Zalman GigaMax III power supply unit 850 W ATX Black

**Brand :** Zalman

**Product code:** ZM850-GV3

**Product name :** GigaMax III

GigaMax III 850W, ATX Ver.3.1, Active PFC, 80 PLUS BRONZE  
 Zalman GigaMax III. Total power: 850 W, AC input voltage: 200 - 240 V, AC input frequency: 50/60 Hz.  
 Cabling type: Semi-Modular. Purpose: PC, Power supply unit (PSU) form factor: ATX, 80 PLUS  
 certification: 80 PLUS Bronze. Product colour: Black, Fan diameter: 12 cm. Compliance certificates: CB,  
 CE, EAC, KC, RCM, RoHS



| Power                              |                                                                                   | Performance                           |                            |
|------------------------------------|-----------------------------------------------------------------------------------|---------------------------------------|----------------------------|
| Total power *                      | 850 W                                                                             | 80 PLUS certification *               | 80 PLUS Bronze             |
| AC input voltage *                 | 200 - 240 V                                                                       | Purpose *                             | PC                         |
| AC input frequency                 | 50/60 Hz                                                                          | Power supply unit (PSU) form factor * | ATX                        |
| Input current                      | 7 A                                                                               | Bearing technology                    | FDB                        |
| Power Factor Correction (PFC) type | Active                                                                            | Mean time between failures (MTBF)     | 100000 h                   |
| Combined power (+3.3V)             | 130 W                                                                             | Design                                |                            |
| Combined power (+12V)              | 850 W                                                                             | Product colour                        | Black                      |
| Combined power (+5V)               | 130 W                                                                             | Fan diameter                          | 12 cm                      |
| Combined power (-12V)              | 3.6 W                                                                             | Operational conditions                |                            |
| Combined power (+5Vsb)             | 15 W                                                                              | Operating temperature (T-T)           | 10 - 40 °C                 |
| Max output current (+3.3V)         | 20 A                                                                              | Certificates                          |                            |
| Max output current (+12V)          | 70.83 A                                                                           | Compliance certificates               | CB, CE, EAC, KC, RCM, RoHS |
| Max output current (+5V)           | 20 A                                                                              | Weight & dimensions                   |                            |
| Max output current (-12V)          | 0.3 A                                                                             | Width                                 | 140 mm                     |
| Max output current (+5Vsb)         | 3 A                                                                               | Depth                                 | 150 mm                     |
| Efficiency                         | 88%                                                                               | Height                                | 86 mm                      |
| Power protection features          | Over current, Over power, Over voltage, Overheating, Short circuit, Under voltage | Weight                                | 1.8 kg                     |
| Ports & interfaces                 |                                                                                   |                                       |                            |
| Cabling type                       | Semi-Modular                                                                      |                                       |                            |



8809213765704

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 11-APR-2026. Prints or copies of Information are only valid on the printed Publication date