



## APC Smart-UPS On-Line SRT2200RMXLI-NC - 2200VA, 8x C13 & 2x C19, rack mount, NMC



**Brand :** APC

**Product code:** SRT2200RMXLI-NC


**Product name :** APC Smart-UPS On-Line SRT2200RMXLI-NC - 2200VA, 8x C13 & 2x C19, rack mount, NMC

APC Smart-UPS On-Line SRT2200RMXLI-NC - 2200VA, 8x C13 & 2x C19, rack mount, NMC  
APC Smart-UPS On-Line SRT2200RMXLI-NC - 2200VA, 8x C13 & 2x C19, rack mount, NMC. UPS topology: Double-conversion (Online), Output power capacity: 2.2 kVA, Output power: 1980 W. AC outlet types: C13 coupler, C19 coupler, AC outlets quantity: 12 AC outlet(s), Serial interface type: RJ-45. Battery technology: Sealed Lead Acid (VRLA), Battery capacity: 367 VAh, Battery life (max): 5 year(s). Form factor: Rackmount, Product colour: Black, Rack capacity: 2U. Compliance certificates: RoHS, Certification: CE, CE Mark, EAC, EN/IEC 62040-1, EN/IEC 62040-2, RCM, VDE

| Features                                       |                            | Design                              |                                                            |
|------------------------------------------------|----------------------------|-------------------------------------|------------------------------------------------------------|
| UPS topology *                                 | Double-conversion (Online) | Rack capacity                       | 2U                                                         |
| Output power capacity *                        | 2.2 kVA                    | Cable length                        | 2.44 m                                                     |
| Output power *                                 | 1980 W                     | Product colour *                    | Black                                                      |
| Waveform *                                     | Sine                       | Display type                        | LCD                                                        |
| Input operation voltage (min) *                | 160 V                      | LED indicators                      | ✓                                                          |
| Input operation voltage (max) *                | 275 V                      | International Protection (IP) code  | IP20                                                       |
| Input frequency *                              | 40 - 70 Hz                 | Operational conditions              |                                                            |
| Output operation voltage (min)                 | 220 V                      | Operating temperature (T-T)         | 0 - 40 °C                                                  |
| Output operation voltage (max)                 | 240 V                      | Storage temperature (T-T)           | -20 - 50 °C                                                |
| Surge energy rating                            | 340 J                      | Operating relative humidity (H-H)   | 0 - 95%                                                    |
| Crest factor                                   | 3:1                        | Storage relative humidity (H-H)     | 0 - 95%                                                    |
| Emergency Power Off (EPO)                      | ✓                          | Operating altitude                  | 0 - 3000 m                                                 |
| Output voltage Total Harmonic Distortion (THD) | 2%                         | Non-operating altitude              | 0 - 15000 m                                                |
| Noise level                                    | 55 dB                      | Certificates                        |                                                            |
| Audible alarm(s)                               | ✓                          | Compliance certificates             | RoHS                                                       |
| Ports & interfaces                             |                            | Certification                       | CE, CE Mark, EAC, EN/IEC 62040-1, EN/IEC 62040-2, RCM, VDE |
| AC outlet types                                | C13 coupler, C19 coupler   | Packaging content                   |                                                            |
| AC outlets quantity                            | 12 AC outlet(s)            | Management card included            | ✓                                                          |
| Number of output IEC jumpers                   | 2                          | Sustainability                      |                                                            |
| USB port                                       | ✓                          | Sustainability certificates         | ENERGY STAR, Green Premium                                 |
| Serial interface                               | ✓                          | Weight & dimensions                 |                                                            |
| Serial interface type                          | RJ-45                      | Width                               | 432 mm                                                     |
| Ethernet LAN (RJ-45) ports                     | 1                          | Depth                               | 584 mm                                                     |
| SmartSlot                                      | ✓                          | Height                              | 85 mm                                                      |
| SmartConnect port                              | ✗                          | Weight                              | 25 kg                                                      |
| Battery                                        |                            | Packaging data                      |                                                            |
| Battery technology                             | Sealed Lead Acid (VRLA)    | Package width                       | 599 mm                                                     |
| Battery capacity                               | 367 VAh                    | Package depth                       | 810 mm                                                     |
| Number of batteries supported                  | 1                          | Package height                      | 246 mm                                                     |
| Battery life (max)                             | 5 year(s)                  | Package weight                      | 34 kg                                                      |
| Battery recharge time                          | 3 h                        | Logistics data                      |                                                            |
| Design                                         |                            | Harmonized System (HS) code         | 85078000                                                   |
| Form factor *                                  | Rackmount                  | Total carbon footprint (kg of CO2e) | 3656.79                                                    |
|                                                |                            | Other features                      |                                                            |
|                                                |                            | Output voltage                      | 230 V                                                      |



0731304327561



731304327561

### Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.