



APC Smart-UPS SMT1500RMI2UNC - 4x C13, USB, rack mountable, NMC, 1500VA



Brand : APC

Product code: SMT1500RMI2UNC

Product name : Smart-UPS SMT1500RMI2UNC - 4x C13, USB, rack mountable, NMC, 1500VA

APC Smart-UPS SMT1500RMI2UNC - 4x C13, USB, rack mountable, NMC, 1500VA

APC Smart-UPS SMT1500RMI2UNC - 4x C13, USB, rack mountable, NMC, 1500VA. UPS topology: Line-Interactive, Output power capacity: 1.5 kVA, Output power: 1000 W. AC outlet types: C13 coupler, C14 coupler, Power plug: C14 coupler, AC outlets quantity: 4 AC outlet(s). Battery technology: Sealed Lead Acid (VRLA), Battery capacity: 432 Ah, Battery recharge time: 3 h. Form factor: Rackmount, Product colour: Black, Rack capacity: 2U. Compliance certificates: RoHS, Certification: CE, EAC, EN/IEC 62040-1, EN/IEC 62040-2, GS Mark, IRAM, RCM, VDE, WEEE


Features		Design	
UPS topology *	Line-Interactive	Product colour *	Black
Output power capacity *	1.5 kVA	Display type	LCD
Output power *	1000 W	LED indicators	✓
Waveform *	Sine	Operational conditions	
Input operation voltage (min) *	151 V	Operating temperature (T-T)	0 - 40 °C
Input operation voltage (max) *	302 V	Storage temperature (T-T)	-15 - 45 °C
Input frequency *	50/60 Hz	Operating relative humidity (H-H)	0 - 95%
Output operation voltage (min)	220 V	Storage relative humidity (H-H)	0 - 95%
Output operation voltage (max)	240 V	Operating altitude	0 - 3000 m
Output frequency	50/60 Hz	Non-operating altitude	0 - 15000 m
Output voltage regulation	5%	Certificates	
Surge energy rating	459 J	Compliance certificates	RoHS
Response time	2 ms	Certification	CE, EAC, EN/IEC 62040-1, EN/IEC 62040-2, GS Mark, IRAM, RCM, VDE, WEEE
Emergency Power Off (EPO)	0	Packaging content	
Noise level	46 dB	Rack mount kit	✓
Audible alarm(s)	✓	Cables included	Input power cable, USB cable
Web-based management	✓	Management card included	✓
Audible alarm modes	Battery replacement	Quick installation guide	✓
Auto-restart	✓	Sustainability	
Ports & interfaces		Sustainability certificates	Green Premium
AC outlet types	C13 coupler, C14 coupler	Weight & dimensions	
Power plug	C14 coupler	Width	432 mm
AC outlets quantity	4 AC outlet(s)	Depth	457 mm
USB 2.0 ports quantity	1	Height	89 mm
Ethernet LAN (RJ-45) ports	1	Weight	28.6 kg
SmartSlot	✓	Packaging data	
SmartConnect port	✗	Resource CD	✓
Battery		Package width	594 mm
Battery technology	Sealed Lead Acid (VRLA)	Package depth	603 mm
Battery capacity	432 Ah	Package height	251 mm
Battery recharge time	3 h	Package weight	31.8 kg
Hot-swap battery	✓	Logistics data	
Automatic battery test	✓	Products per pallet	8 pc(s)
Cold start	✓	Harmonized System (HS) code	85078000
Design		Total carbon footprint (kg of CO2e)	1407.66
Form factor *	Rackmount		
Rack capacity	2U		

Other features

Output voltage	230 V
----------------	-------



0731304327684



731304327684

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.