

Chieftec CTG-550C power supply unit 550 W 20+4 pin ATX ATX Black

Brand : Chieftec

Product code: CTG-550C

Product name : CTG-550C

550W, 230V/6A, ATX 12V 2.3, PS II, >85%, 120mm fan

Chieftec CTG-550C power supply unit 550 W 20+4 pin ATX ATX Black:

this popular PSU series is now extended by new models featuring cable management. With many awards granted, these PSUs are perfectly suited for cost aware users, who pay attention to both good price and high efficiency.

Chieftec CTG-550C. Total power: 550 W, AC input voltage: 230 V, AC input frequency: 50 Hz. Motherboard power connector: 20+4 pin ATX, Cabling type: Semi-Modular. Purpose: PC, Power supply unit (PSU) form factor: ATX, 80 PLUS certification: 80 PLUS. Product colour: Black, Cooling type: Active, Fan diameter: 12 cm. Compliance certificates: RoHS, Certification: CE, CB, FCC



Power		Ports & interfaces	
Total power *	550 W	CPU P4 connector (4-pin)	1
AC input voltage *	230 V	Floppy drive power connector	2
AC input frequency	50 Hz	Cabling type	Semi-Modular
Input current	6 A	Performance	
Maximum input current (@110V)	+12V1,+12V2,+3.3V,+5V,+5Vsb,-12V	80 PLUS certification *	80 PLUS
Power factor	0.9	Purpose *	PC
Power Factor Correction (PFC) type	Active	Power supply unit (PSU) form factor *	ATX
Combined power (+3.3V)	130 W	ATX version	2.3
Combined power (+12V)	456 W	Mean time between failures (MTBF)	100000 h
Combined power (+5V)	130 W	Design	
Combined power (-12V)	3.6 W	Product colour	Black
Combined power (+5Vsb)	15 W	Cooling type	Active
Max output current (+3.3V)	25 A	Fan diameter	12 cm
Max output current (+12V1)	25 A	Number of fans	1 fan(s)
Max output current (+12V2)	25 A	Fan location	Top
Max output current (+5V)	22 A	Certificates	
Max output current (-12V)	0.3 A	Compliance certificates	RoHS
Max output current (+5Vsb)	3 A	Certification	CE, CB, FCC
Efficiency	85%	Weight & dimensions	
Power protection features	Over current, Over voltage, Overheating, Overload, Short circuit, Under voltage	Width	150 mm
Ports & interfaces		Depth	140 mm
Motherboard power connector *	20+4 pin ATX	Height	87 mm
Number of SATA power connectors	6	Packaging data	
Peripheral (Molex) power connectors (4-pin) *	4	Package type	Box
EPS power connector (8-pin)	✓	Logistics data	
PCI Express power connectors (6+2 pin)	2	Harmonized System (HS) code	84733020
Other features			
Parallel processing technology support		2-Way CrossFireX, 2-Way SLI	



4710713239364

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.