

Epson WorkForce WF-7830DTWF Inkjet A3 4800 x 2400 DPI Wi-Fi

Brand : Epson

Product family: WorkForce

Product code: C11CH68403

Product name : WF-7830DTWF

A3, Print, Scan, Copy, Fax, 4800 x 2400 DPI, USB, LAN, WLAN, Touchscreen, 18.2 kg
 Epson WorkForce WF-7830DTWF. Print technology: Inkjet, Printing: Colour printing, Maximum resolution: 4800 x 2400 DPI. Scanning: Colour scanning, Optical scanning resolution: 1200 x 2400 DPI. Faxing: Colour faxing. Maximum ISO A-series paper size: A3. Wi-Fi. Product colour: Black



Printing		Ports & interfaces	
Duplex printing mode	Auto	USB port	✓
Print technology *	Inkjet	Network	
Printing *	Colour printing	Wi-Fi *	✓
Duplex printing *	✓	Ethernet LAN *	✓
Maximum resolution *	4800 x 2400 DPI	Wi-Fi standards	802.11b, 802.11g, Wi-Fi 4 (802.11n)
Print speed (ISO/IEC 24734) black	25 ppm	Security algorithms	64-bit WEP, 128-bit WEP, WPA-PSK, WPA-TKIP, WPA-AES
Print speed (ISO/IEC 24734) colour	12 ppm	Management protocols	SNMP, HTTP, DHCP, BOOTP, APIPA, DDNS, mDNS, SNMP, SLP, WSD, LLTD, Ping
Duplex print speed (black, normal quality, A4/US Letter)	16 ppm	Mobile printing technologies	Epson Connect, Epson iPrint, Epson Email Print, Epson Remote Print, Apple AirPrint, Mopria Print Service
Duplex print speed (colour, normal quality, A4/US Letter)	9 ppm	Performance	
Duplex print speed (ISO/IEC 24734, A4) black	16 ppm	Card reader integrated	✗
Duplex print speed (ISO/IEC 24734, A4) colour	9 ppm	Design	
Borderless printing	✓	Product colour *	Black
Scanning		Market positioning *	Home & office
Duplex scanning *	✓	Built-in display *	✓
Scanning *	Colour scanning	Display	LCD
Optical scanning resolution *	1200 x 2400 DPI	Display diagonal	6.86 cm (2.7")
Scan technology	CIS	Touchscreen	✓
Scan to	Cloud	Colour display	✓
Image formats supported	BMP, JPEG, TIFF, PNG	Power	
Document formats supported	PDF	Power consumption (copying)	20 W
Fax		Power consumption (ready)	8.8 W
Faxing *	Colour faxing	Power consumption (off)	0.2 W
Fax transmission speed	3 sec/page	System requirements	
Modem speed	33.6 Kbit/s	Windows operating systems supported	✓
Fax memory	180 pages		
Auto-redialing	✓		
Speed dialling	✓		
Fax speed dialling (max numbers)	100		

Fax		System requirements	
Fax forwarding	✓	Mac operating systems supported	✓
Fax forwarding to	PC	Weight & dimensions	
Error Correction Mode (ECM)	✓	Width	515 mm
Features		Depth	400 mm
Recommended duty cycle	200 - 2500 pages per month	Height	350 mm
Maximum duty cycle *	50000 pages per month	Weight	18.2 kg
Number of print cartridges *	4	Packaging data	
Printing colours *	Black, Cyan, Magenta, Yellow	Package width	475 mm
Page description languages	ESC/P-R	Package depth	590 mm
Country of origin	Indonesia	Package height	465 mm
Input & output capacity		Package weight	21.6 kg
Total number of input trays *	2	Quantity per pack	1 pc(s)
Total output capacity *	125 sheets	Packaging content	
Multi-Purpose tray	✓	Cartridge(s) included	✓
Multi-Purpose tray input capacity	500 sheets	Cables included	AC
Auto document feeder (ADF)	✓	Drivers included	✓
Auto document feeder (ADF) input capacity	50 sheets	Warranty card	✓
Maximum input capacity	500 sheets	Logistics data	
Paper handling		Harmonized System (HS) code	84433100
Maximum ISO A-series paper size *	A3	Pallet gross weight	0 g
Paper tray media types *	Thick paper	Products per pallet layer	2 pc(s)
ISO A-series sizes (A0...A9) *	A3, A4, A5, A6	Products per pallet	8 pc(s)
ISO B-series sizes (B0...B9)	B4, B5	Pallet weight (UK)	0 g
Non-ISO print media sizes	Legal, Letter	Products per pallet layer (UK)	4 pc(s)
Envelopes sizes	C4, C6, DL	Products per pallet (UK)	16 pc(s)
Photo paper sizes	9x13,10x15,13x18	Other features	
Paper tray media weight	64 - 255 g/m²	Printing method	Epson PrecisionCore
		Number of users	5 user(s)
		Compatible operating systems	Mac OS 10.5.8 oder höher, Windows 10, Windows 7, Windows 8, Windows Server 2003 (32/64 Bit), Windows Server 2008 (32/64 Bit), Windows Server 2008 R2, Windows Server 2012 (64bit), Windows Vista, Windows XP, Windows Server 2003 R2
		Ink drop	3.8
		Fax polling	✓
		Print head nozzles	800 nozzles black, 256 nozzles per colour
		Supported network protocols	TCP/IPv4, TCP/IPv6



8715946668420

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.