

Lanview LVN6010SOUT networking cable Black 10 m Cat6a S/FTP (S-STP)

Brand : Lanview

Product code: LVN6010SOUT

Product name : LVN6010SOUT

- Designed in Denmark
 - VERY soft & flexible
 - Thermal Range: -40° to 85°C
 - Acid, Oil, Microbe, Chemical, UV & Hydrolysis resistance
 - Suitable for Voice, Data, Video application
- Cat6a HIGH-FLEX S/FTP Outdoor Network Cable 10m

Lanview LVN6010SOUT networking cable Black 10 m Cat6a S/FTP (S-STP):

CAT6A HIGH-FLEX S/FTP Outdoor Network Cable

Lanview HIGH-FLEX PUR patch cable is designed for industrial or outdoor environments. PUR cables are ideally applied for harsh areas with great benefits of UV and oil resistant. Lanview PUR cables meet Class EA/500MHz up to 10G Ethernet, suitable for Voice,Data,Video applications.

HIGHLY Flexible & Fluke DSX-8000 Channel compliant.

Lanview LVN6010SOUT. Cable length: 10 m, Cable standard: Cat6a, Cable shielding: S/FTP (S-STP), Connector 1: RJ-45, Connector 2: RJ-45, Connector contacts plating: Gold, Data transfer rate: 10000 Mbit/s, Product colour: Black



Features

Product colour *	Black
Cable length *	10 m
Cable standard *	Cat6a
Cable shielding *	S/FTP (S-STP)
Connector 1 *	RJ-45
Connector 2 *	RJ-45
Connector 1 gender *	Male
Connector 2 gender *	Male
Connector contacts plating	Gold
Connector shielding	✓
Connector shield material	Copper alloy
Jacket material	Polyurethane (PUR)
Cable shape	Round
Conductor material	Copper
Ethernet interface type	10 Gigabit Ethernet
AWG wire size	26
Data transfer rate	10000 Mbit/s
Frequency	500 MHz
Power over Ethernet (PoE)	✓

Features

Power over Ethernet (PoE) type supported	PoE+
Suitable for outdoor use	✓
Oil-resistant	✓
Molded cable boot	✓
Snagless cable boot	✓
Plug and Play	✓
Country of origin	China

Operational conditions

Operating temperature (T-T)	-40 - 85 °C
-----------------------------	-------------

Certificates

Compliance certificates	RoHS
Certification	RoHS, CE

Weight & dimensions

Weight	360 g
--------	-------

Packaging data

Package weight	364 g
----------------	-------

Other features

Cable diameter	6 mm
----------------	------



5704174654117

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.