

NETGEAR M4300-8X8F Managed L3 10G Ethernet
(100/1000/10000) 1U Black

Brand : NETGEAR

Product code: XSM4316S-100NES

Product name : M4300-8X8F

320 Gbps, 10/100/1000/10000, 1U, L3

NETGEAR M4300-8X8F. Switch type: Managed, Switch layer: L3. Basic switching RJ-45 Ethernet ports type: 10G Ethernet (100/1000/10000), Basic switching RJ-45 Ethernet ports quantity: 8, USB 2.0 ports quantity: 1, Console port: RJ-45/Mini-USB. MAC address table: 16000 entries, Switching capacity: 320 Gbit/s. Networking standards: IEEE 802.11ad, IEEE 802.11az, IEEE 802.3ad, IEEE 802.3az. Rack mounting, Form factor: 1U



Management features

Switch type *	Managed
Switch layer	L3
Quality of Service (QoS) support	✓
Web-based management	✓
ARP inspection	✓

Ports & interfaces

Basic switching RJ-45 Ethernet ports quantity *	8
Basic switching RJ-45 Ethernet ports type *	10G Ethernet (100/1000/10000)
SFP+ module slots quantity	8
Fiber optic connector	SFP+
Console port	RJ-45/Mini-USB
USB 2.0 ports quantity	1

Network

Networking standards *	IEEE 802.11ad, IEEE 802.11az, IEEE 802.3ad, IEEE 802.3az
10G support *	✓
Cable types supported	Cat5, Cat5e, Cat6, Cat7
Port mirroring	✓
IP routing	✓
Flow control support	✓
Link aggregation	✓
Rate limiting	✓
Auto MDI/MDI-X	✓
Spanning tree protocol	✓
Auto-sensing	✓
Auto-negotiation	✓
VLAN support	✓
Virtual LAN features	Private VLAN

Optical fiber

Fiber ethernet cabling technology	10GBASE-LR, 10GBASE-LRM, 10GBASE-SR
-----------------------------------	-------------------------------------

Multicast features

Number of multicast groups filtered	4000
-------------------------------------	------

Design

Rack mounting *	✓
Stackable *	✓
Form factor	1U
Product colour	Black
LED indicators	Activity, Power, Speed
Safety	CSA 22.2 #950, UL 1950)/cUL IEC 950/EN 60950
Electromagnetic compatibility	CE, FCC 15 A, VCCI A, A EN 55022, (CISPR 22) A, EN 50082-1, EN 55024

Performance

Built-in processor	✓
Processor frequency	800 MHz
Internal memory	1024 MB
Flash memory	256 MB
Noise level	36.9 dB
Mean time between failures (MTBF)	196120 h

Power

Power supply included *	✓
Number of power supply units	1
AC input voltage	120 - 230 V
Power consumption (max)	49 W

Power over Ethernet (PoE)

Power over Ethernet (PoE) *	✗
-----------------------------	---

Operational conditions

Operating temperature (T-T)	0 - 50 °C
Storage temperature (T-T)	-20 - 70 °C
Operating relative humidity (H-H)	0 - 90%
Storage relative humidity (H-H)	0 - 95%
Operating altitude	0 - 3000 m
Non-operating altitude	0 - 3000 m
Heat dissipation	18577 BTU/h

Data transmission		Weight & dimensions	
Switching capacity *	320 Gbit/s	Width	212 mm
Forwarding rate	357 Mpps	Depth	345 mm
MAC address table *	16000 entries	Height	44 mm
Store-and-forward	✓	Weight	3.32 kg
Number of static routes	64	Packaging content	
Jumbo frames support	✓	Cables included	AC, LAN (RJ-45), Mini-USB
Jumbo frames	9000	User guide	✓
Security		Rack mount kit	✓
DHCP features	DHCP server, DHCP client	Packaging data	
Access Control List (ACL)	✓	Rubber feet	✓
Security algorithms	HTTPS, SNMP, SSH	Resource CD	✓
SSH/SSL support	✓	Logistics data	
BPDU filtering/protection	✓	Harmonized System (HS) code	85176990
Multicast features			
Multicast support	✓		



0606449110005



606449110005

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.