



COUGAR Power Supply GEX PRO 650W ATX3.1 / 80 Plus Gold / Modular

Brand : COUGAR

Product code: 31GP065001P01

Product name : Power Supply GEX PRO 650W ATX3.1 / 80 Plus Gold / Modular

- Supports PCI Express 5.1 Graphics Cards with 12+4 Pin Connector for true 200% power excursion dynamic outputs
 - 80 PLUS Gold Certified for up to 91% efficiency in power conversion, reducing electricity bills
 - Durable HDB Fan with Hydro Dynamic Bearing groundbreaking grooved fan blade design lets you experience noiseless gaming
 - It includes 105°C Japanese capacitors for standby power to ensure keep providing computer with stable electrical supply
 - At 140mm in length, GEX PRO is one of the most compact fully modular PSU. This means it will fit in a wide range of cases, and give you additional flexibility for building your PC
 - Compatible with the Latest PC Technology, designed for users with current and next-generation multi-core CPU platforms
 - Powerful performance even at 40°C ambient temperature
 - Gold Cybenetics rating for efficiency(750W/850W)
 - A+ Cybenetics rating for noise level. (750W/850W)
- 650 W, AC100-240V, 50-60Hz, 10-5A, ATX 3.1, 80 PLUS Gold



Power		Ports & interfaces	
Total power *	650 W	Cabling type	Fully-Modular
AC input voltage *	100 - 240 V	Performance	
AC input frequency	50/60 Hz	80 PLUS certification *	80 PLUS Gold
Input current	10-5 A	Purpose *	PC
Combined power (+3.3V)	100 W	Power supply unit (PSU) form factor *	ATX
Combined power (+12V)	649.2 W	ATX version	3.1
Combined power (+5V)	100 W	Bearing technology	HDB
Combined power (-12V)	3.6 W	Design	
Combined power (+5Vsb)	15 W	Product colour	Black
Max output current (+3.3V)	20 A	Cooling type	Active
Max output current (+12V)	54.1 A	Fan diameter	12 cm
Max output current (+5V)	20 A	Number of fans	1 fan(s)
Max output current (-12V)	0.3 A	Fan location	Top
Max output current (+5Vsb)	3 A	On/off switch	✓
Efficiency	91%	Operational conditions	
Power protection features	Over current, Over power, Over voltage, Overheating, Short circuit, Under voltage	Operating temperature (T-T)	10 - 40 °C
Ports & interfaces		Storage temperature (T-T)	-40 - 70 °C
Motherboard power connector *	20+4 pin ATX	Operating relative humidity (H-H)	20 - 85%
Motherboard power cable length	61 cm	Storage relative humidity (H-H)	5 - 95%
Number of SATA power connectors	8	Certificates	
Number of PATA power connectors	3	Compliance certificates	CE, EAC, Federal Communications Commission (FCC), RoHS, UKCA
SATA power cable length	400,520,640,760 mm	Weight & dimensions	
PCI Express power connectors (6+2 pin)	2	Width	150 mm
PCI Express power connectors (12+4 pin)	1	Depth	140 mm
PCI Express power connectors (12+4 pin) cable length	650 mm	Height	56 mm
CPU power connector (4+4 pin)	✓	Weight	2.05 kg
CPU power cable length	70 cm	Packaging data	
PCI Express connector	✓	Package width	215 mm

Packaging data

Package depth	330 mm
Package height	107 mm
Package weight	2.07 kg
Package type	Box



4710483778698



0192554008561



192554008561



4541995039171

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.