

NETGEAR GS728TX L2/L3 10G Ethernet (100/1000/10000) Black

Brand : NETGEAR

Product code: GS728TX-300EUS

Product name : GS728TX

24 GE ports, 4 10G ports, 440 x 257 x 43.2 mm, 3.8 kg  
NETGEAR GS728TX. Switch layer: L2/L3. Basic switching RJ-45 Ethernet ports type: 10G Ethernet (100/1000/10000), Basic switching RJ-45 Ethernet ports quantity: 24, Installed SFP+ modules quantity: 4. Full duplex. MAC address table: 16000 entries. Networking standards: IEEE 802.1D, IEEE 802.1Q, IEEE 802.1ab, IEEE 802.1p, IEEE 802.1s, IEEE 802.1w, IEEE 802.3, IEEE.... Rack mounting



| Management features                             |                                                                                                                                                                                                        | Security                          |             |
|-------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------|-------------|
| Switch layer                                    | L2/L3                                                                                                                                                                                                  | MAC address filtering             | ✓           |
| Ports & interfaces                              |                                                                                                                                                                                                        | SSH/SSL support                   | ✓           |
| Basic switching RJ-45 Ethernet ports quantity * | 24                                                                                                                                                                                                     | Design                            |             |
| Basic switching RJ-45 Ethernet ports type *     | 10G Ethernet (100/1000/10000)                                                                                                                                                                          | Rack mounting *                   | ✓           |
| Installed SFP+ modules quantity *               | 4                                                                                                                                                                                                      | Stackable *                       | ✓           |
| SFP+ module slots quantity                      | 4                                                                                                                                                                                                      | Product colour                    | Black       |
| Network                                         |                                                                                                                                                                                                        | Performance                       |             |
| Networking standards *                          | IEEE 802.1D, IEEE 802.1Q, IEEE 802.1ab, IEEE 802.1p, IEEE 802.1s, IEEE 802.1w, IEEE 802.3, IEEE 802.3ab, IEEE 802.3ad, IEEE 802.3af, IEEE 802.3at, IEEE 802.3az, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z | Built-in processor                | ✓           |
|                                                 |                                                                                                                                                                                                        | Processor frequency               | 800 MHz     |
| 10G support *                                   | ✓                                                                                                                                                                                                      | Flash memory                      | 64 MB       |
| Port mirroring                                  | ✓                                                                                                                                                                                                      | Noise level                       | 26.8 dB     |
| Full duplex                                     | ✓                                                                                                                                                                                                      | Mean time between failures (MTBF) | 1252990 h   |
| Flow control support                            | ✓                                                                                                                                                                                                      | Power                             |             |
| Link aggregation                                | ✓                                                                                                                                                                                                      | Power consumption (typical)       | 748.18 W    |
| Broadcast storm control                         | ✓                                                                                                                                                                                                      | Power over Ethernet (PoE)         |             |
| Rate limiting                                   | ✓                                                                                                                                                                                                      | Power over Ethernet (PoE) *       | ✗           |
| Spanning tree protocol                          | ✓                                                                                                                                                                                                      | Operational conditions            |             |
| VLAN support                                    | ✓                                                                                                                                                                                                      | Operating temperature (T-T)       | 0 - 50 °C   |
| Virtual LAN features                            | Voice VLAN                                                                                                                                                                                             | Storage temperature (T-T)         | -20 - 70 °C |
| Number of VLANs                                 | 256                                                                                                                                                                                                    | Operating relative humidity (H-H) | 0 - 95%     |
| Data transmission                               |                                                                                                                                                                                                        | Storage relative humidity (H-H)   | 0 - 95%     |
| MAC address table *                             | 16000 entries                                                                                                                                                                                          | Operating altitude                | 0 - 3000 m  |
| Static route                                    | ✓                                                                                                                                                                                                      | Non-operating altitude            | 0 - 3000 m  |
| Number of static routes                         | 32                                                                                                                                                                                                     | Weight & dimensions               |             |
| Packet buffer memory                            | 16 MB                                                                                                                                                                                                  | Width                             | 440 mm      |
| Security                                        |                                                                                                                                                                                                        | Depth                             | 257 mm      |
| DHCP features                                   | DHCP client                                                                                                                                                                                            | Height                            | 43.2 mm     |
| Access Control List (ACL)                       | ✓                                                                                                                                                                                                      | Weight                            | 3.8 kg      |
| Access Control List (ACL) ingress               | 100                                                                                                                                                                                                    | Packaging content                 |             |
| IGMP snooping                                   | ✓                                                                                                                                                                                                      | Cables included                   | AC          |
|                                                 |                                                                                                                                                                                                        | Manual                            | ✓           |



0606449173147



606449173147

### Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.