

CyberPower PR750ERT2UC uninterruptible power supply (UPS) Line-Interactive 0.75 kVA 750 W 10 AC outlet(s)

Brand : CyberPower

Product code: PR750ERT2UC

Product name : PR750ERT2UC



- Line-interactive UPS Topology
 - Active PFC Compatible
 - Toolless Battery Replacement
 - High Output Power Factor
 - Overload Protection
 - Quick Charging Technology
 - Surge and Spike Protection
 - LCD Status Display
 - Serial Connectivity Port
 - PowerPanel Management Software
 - Built-in Remote Cloud Card by Ethernet
 - Energy Saving Technology
 - Pure Sine Wave Output
 - Battery Management Technology
 - Automatic Voltage Regulation (AVR)
 - Critical/Non-critical Load Outlets
 - Hot-swappable Batteries
 - EMI and RFI Filtration
 - USB Connectivity Port
 - Emergency Power Off (EPO) Port
 - SNMP/HTTP Remote Management Capability (Optional)
- Smart App UPS for Network and Server



Features		Battery	
UPS topology *	Line-Interactive	Typical backup time at full load	6.4 min
Output power capacity *	0.75 kVA	Typical backup time at half load	20 min
Output power *	750 W	Battery recharge time	3 h
Waveform *	Pure sine	Hot-swap battery	✓
Input operation voltage (min) *	200 V	Design	
Input operation voltage (max) *	240 V	Form factor *	Rackmount/Tower
Input frequency *	50/60 Hz	Housing material	Metal
Output operation voltage (min)	220 V	Rack capacity	2U
Output operation voltage (max)	240 V	Extended battery module rack capacity	2U
Output frequency	50/60 Hz	Cable length	3.05 m
Automatic Voltage Regulation (AVR)	✓	Cooling type	Active
Maximum current	16 A	Built-in fan	✓
Surge energy rating	2430 J	Product colour *	Black
Response time	6 ms	Control type	Buttons
Heat dissipation	96.7 BTU/h	Display type	LCD
Number of input phases	1	LED indicators	✓
Number of output phases	1	Operational conditions	
Output power factor	1	Operating temperature (T-T)	0 - 40 °C
Power Factor Correction (PFC) type	Active	Storage temperature (T-T)	-15 - 45 °C
Emergency Power Off (EPO)	✓	Operating relative humidity (H-H)	0 - 95%
EMI/RFI noise filtering	✓	Storage relative humidity (H-H)	0 - 95%
Surge protection	✓	Operating altitude	0 - 3000 m
Power protection features	Overload	Non-operating altitude	0 - 15000 m
Audible alarm modes	Alarm when on battery, Fault, Low battery alarm, Overload alarm	Certificates	
Power source type	AC	Compliance certificates	
Detachable power cord	✓	CE, Federal Communications Commission (FCC), RCM, RoHS, UL, VCCI	

Ports & interfaces		Packaging content	
AC outlet types	C13 coupler	Batteries included	✓
Power plug	C14 coupler	Rack mount kit	✓
AC outlets quantity	10 AC outlet(s)	Cables included	Serial
USB port	✓	Manual	✓
USB 2.0 ports quantity	1	Sustainability	
USB port type	USB Type-B	Sustainability compliance	✓
Serial interface	✓	Weight & dimensions	
Serial interface type	RS-232	Width	433 mm
Serial ports quantity	2	Depth	500 mm
RS-232 ports	2	Height	86.5 mm
Ethernet LAN (RJ-45) ports	2	Weight	32 kg
Emergency Power Off (EPO) connector	✓	Packaging data	
Battery		Package width	560 mm
Battery technology	Sealed Lead Acid (VRLA)	Package depth	620 mm
Number of batteries supported	1	Package height	275 mm
		Package weight	38.8 kg
		Package type	Box
		Logistics data	
		Country of origin	China
		Other features	
		Battery type	RBP0128



4711027798851

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.