



InLine PoE+ Gigabit Network Switch 24 port, 1 Gb/s, 2xSFP,19"1U(incl. brackets)

Brand : InLine

Product code: 32316P



Product name : InLine PoE+ Gigabit Network Switch 24 port, 1 Gb/s, 2xSFP,19"1U(incl. brackets)

InLine PoE+ Gigabit Network Switch 24 port, 1 Gb/s, 2xSFP,19"1U(incl. brackets)
InLine PoE+ Gigabit Network Switch 24 port, 1 Gb/s, 2xSFP,19"1U(incl. brackets). Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000), Basic switching RJ-45 Ethernet ports quantity: 16. MAC address table: 8000 entries. Networking standards: IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3az, IEEE 802.3bt, IEEE 802.3u,.... Power connector: AC-in jack. Power over Ethernet (PoE). Rack mounting, Form factor: 1U

Ports & interfaces		Performance	
Basic switching RJ-45 Ethernet ports quantity *	16	Maximum data transfer rate	1000 Mbit/s
Basic switching RJ-45 Ethernet ports type *	Gigabit Ethernet (10/100/1000)	Power	
SFP module slots quantity	2	Power supply included *	✓
Power connector	AC-in jack	AC input voltage	100 - 240 V
Network		AC input frequency	50 - 60 Hz
Networking standards *	IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3az, IEEE 802.3bt, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z	Power consumption (typical)	330 W
	10G support *	✗	
	Copper ethernet cabling technology	10BASE-T, 100BASE-TX, 1000BASE-T	
Cable types supported	Cat5e, Cat6, Cat6a, Cat8.1	Power over Ethernet (PoE)	
Auto MDI/MDI-X	✓	Power over Ethernet (PoE) *	✓
Ethernet LAN data rates	10,100,1000 Mbit/s	Power over Ethernet plus (PoE+) ports quantity	8
MAC address auto-learning supported	✓	Total Power over Ethernet (PoE) budget	300 W
Optical fiber		Other features	
Fiber ethernet cabling technology	1000BASE-X	Dimensions (WxDxH)	440 x 37.75 x 230 mm
Data transmission		Ethernet interface type	Fast Ethernet, Gigabit Ethernet
Forwarding rate	26.78 Mpps	Ethernet LAN (RJ-45) ports	16
MAC address table *	8000 entries	Operational conditions	
Jumbo frames support	✓	Operating temperature (T-T)	-10 - 60 °C
Jumbo frames	9216	Storage temperature (T-T)	-40 - 70 °C
Transmission method	Store-and-forward	Operating relative humidity (H-H)	10 - 90%
Packet buffer memory	4.1 MB	Storage relative humidity (H-H)	5 - 90%
Design		Weight & dimensions	
Rack mounting *	✓	Width	440 mm
Form factor	1U	Depth	37.8 mm
Product colour	Black	Height	230 mm
LED indicators	✓	Weight	4.5 kg
Number of fans	3 fan(s)	Packaging data	
		Package width	350 mm
		Package depth	500 mm
		Package height	95 mm
		Package weight	3.12 kg

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 12-APR-2026. Prints or copies of Information are only valid on the printed Publication date