



APC BX1000M uninterruptible power supply (UPS) Line-Interactive 1 kVA 600 W 8 AC outlet(s)

Brand : APC

Product code: BX1000M

Product name : BX1000M

1000 VA, 600 W, 120 V, 4 x NEMA 5-15R(Battery Backup), 4 x NEMA 5-15R(selector_surgetitle), 88 - 139 V, 50/60 Hz, 1103 J, 1.83 m, Black


APC BX1000M. UPS topology: Line-Interactive, Output power capacity: 1 kVA, Output power: 600 W. AC outlet types: NEMA 5-15R, AC outlets quantity: 8 AC outlet(s), Serial interface type: RJ-45. Battery technology: Sealed Lead Acid (VRLA), Battery life (max): 5 year(s), Battery recharge time: 12 h. Form factor: Tower, Product colour: Black, Cable length: 1.83 m. Compliance certificates: RoHS, Certification: California (CEC) Battery Charger, FCC Part 15 Class B, UL 1778



Features		Design	
UPS topology *	Line-Interactive	Form factor *	Tower
Output power capacity *	1 kVA	Cable length	1.83 m
Output power *	600 W	Product colour *	Black
Waveform *	Sine	Operational conditions	
Input operation voltage (min) *	88 V	Operating temperature (T-T)	0 - 40 °C
Input operation voltage (max) *	139 V	Storage temperature (T-T)	-15 - 45 °C
Input frequency *	60 Hz	Operating relative humidity (H-H)	0 - 95%
Output operation voltage (max)	120 V	Storage relative humidity (H-H)	0 - 95%
Output frequency regulation	60 Hz	Certificates	
Maximum current	12 A	Compliance certificates	RoHS
Surge energy rating	1103 J	Certification	California (CEC) Battery Charger, FCC Part 15 Class B, UL 1778
Ports & interfaces		Sustainability	
AC outlet types	NEMA 5-15R	Sustainability certificates	ENERGY STAR
AC outlets quantity	8 AC outlet(s)	Weight & dimensions	
Serial interface	✓	Width	91 mm
Serial interface type	RJ-45	Depth	310 mm
Ethernet LAN (RJ-45) ports	1	Height	190 mm
Cabling technology	10/100/1000Base-T(X)	Weight	7.2 kg
Battery		Packaging data	
Battery technology	Sealed Lead Acid (VRLA)	Package width	142 mm
Battery life (max)	5 year(s)	Package depth	442 mm
Battery recharge time	12 h	Package height	253 mm
		Package weight	8 kg



0731304331766



731304331766

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.