



InLine 76619F interface cards/adapter Internal Serial


Brand : InLine

Product code: 76619F

Product name : 76619F

InLine PCIe 2-port RS-232 card, 2x D-Sub 9 connector, incl. low-profile

InLine 76619F. Host interface: PCIe, Output interface: Serial, Host interface gender: Male. Purpose: PC, Country of origin: Taiwan. Chipset: CH382L, Baud rate: 921.6 Kbit/s, FIFO (First In, First Out): 256 B. Windows operating systems supported: Windows 10, Windows 11, Windows 7, Windows 8, Windows 8.1, Windows XP, Linux operating systems supported: Kernel 2.6, Kernel 2.6.31, Kernel 2.6.33, Kernel 3.12, Kernel 3.17, Kernel 3.3, Kernel 4.6.4,..., Server operating systems supported: Windows Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2013, Windows.... Width: 85 mm, Depth: 85 mm, Height: 20 mm



Ports & interfaces		System requirements	
Host interface *	PCIe	Windows operating systems supported	Windows 10, Windows 11, Windows 7, Windows 8, Windows 8.1, Windows XP
Host interface gender	Male		
Output interface *	Serial	Linux operating systems supported	Kernel 2.6, Kernel 2.6.31, Kernel 2.6.33, Kernel 3.12, Kernel 3.17, Kernel 3.3, Kernel 4.6.4, Linux Kernel 5.10, Linux Kernel 5.11, Linux Kernel 5.12, Linux Kernel 5.13, Linux Kernel 5.14, Linux Kernel 5.15, Linux Kernel 5.19, Linux Kernel 5.4, Linux Kernel 5.8, Linux Kernel 5.9, Linux Kernel 6.2, Linux Kernel 6.5, Linux Mint 10, Linux Mint 11, Linux Mint 12, Linux Mint 13, Linux Mint 17, Linux Mint 17.1, Linux Mint 17.2, Linux Mint 18.3, Linux Mint 9
Expansion card standard	PCIe 2.0		
Serial ports quantity	2	Server operating systems supported	Windows Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2013, Windows Server 2016, Windows Server 2019, Windows Server 2022
Serial interface type	RS-232, 9-pin		
Design		Technical details	
Internal *	✓	Compliance certificates	
Purpose	PC	CE, Federal Communications Commission (FCC), TÜV mark	
Country of origin	Taiwan	Weight & dimensions	
Features		Width	85 mm
Chipset	CH382L	Depth	85 mm
Baud rate	921.6 Kbit/s	Height	20 mm
FIFO (First In, First Out)	256 B	Weight	12 kg
Data bits	5, 6, 7, 8	Packaging data	
Stop bits	1, 2	Mounting brackets included	
Full duplex	✓	✓	
Parity bit	Even, Mark, No, Odd, Space		
Operational conditions			
Operating temperature (T-T)	0 - 55 °C		
Storage temperature (T-T)	-40 - 70 °C		

Packaging data	
Drivers included	✓
Package weight	49 g
Package volume	1000 cm ³
Other features	
Electrostatic Discharge (ESD) protection	15 kV



4043718348282

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.