



DELL Pro P P2426E computer monitor 61.2 cm (24.1") 1920 x 1200 pixels WUXGA LCD Black

Brand : DELL

Product family: Pro P

Product code: DELL-P2426E

Product name : P2426E

- 24.1" LCD IPS
 - WUXGA, 16:10, 1920 x 1200
 - 100Hz, 5ms
 - USB Hub, USB PD (96W)
- 24.1", 1920 x 1200 Edge LED IPS, 100Hz, 16:10, 5ms, 178°/178°, USB PD (96W)

DELL Pro P P2426E computer monitor 61.2 cm (24.1") 1920 x 1200 pixels WUXGA LCD Black:

Equipped for seamless productivity, this 24-inch 16:10 FHD hub monitor offers extensive connectivity, up to 100W of power delivery, and TÜV-certified 4-star eye comfort.

DELL Pro P P2426E. Display diagonal: 61.2 cm (24.1"), Display resolution: 1920 x 1200 pixels, HD type: WUXGA, Display technology: LCD, Response time: 8 ms, Native aspect ratio: 16:10, Viewing angle, horizontal: 178°, Viewing angle, vertical: 178°. Built-in USB hub. VESA mounting, Height adjustment. Product colour: Black



Display		Ports & interfaces	
Display diagonal *	61.2 cm (24.1")	HDCP	✓
Display resolution *	1920 x 1200 pixels	HDCP version	1.4
HD type *	WUXGA	Network	
Native aspect ratio *	16:10	Ethernet LAN	✓
Display technology *	LCD	Ergonomics	
Panel type *	IPS	VESA mounting *	✓
LED backlight	✓	Panel mounting interface	100 x 100 mm
Backlight type	Edge LED	Cable management	✓
Touchscreen *	✗	Cable lock slot *	✓
Display brightness (peak)	300 cd/m²	Cable lock slot type	Kensington
Response time *	8 ms	Height adjustment *	✓
Response time measurement type	GTG (Gray to Gray)	Adjustable height (max)	15 cm
Anti-glare screen	✓	Pivot	✓
Screen shape *	Flat	Pivot angle	-90 - 90°
Supported graphics resolutions	640 x 480 (VGA), 720 x 400, 800 x 600 (SVGA), 1024 x 768 (XGA), 1152 x 864 (XGA+), 1280 x 1024 (SXGA), 1600 x 900, 1920 x 1080 (HD 1080), 1920 x 1200 (WUXGA)	Swivelling	✓
		Swivel angle range	-45 - 45°
Supported video modes	1080p, 720p, 576p, 480p	Tilt adjustment	✓
Contrast ratio (typical) *	1500:1	Tilt angle range	-5 - 21°
Maximum refresh rate *	100 Hz	Power	
Viewing angle, horizontal	178°	Energy efficiency class (SDR) *	D
Viewing angle, vertical	178°	Energy efficiency class (HDR) *	Not available
Display number of colours *	16.7 million colours	Energy consumption (SDR) per 1000 hours *	15 kWh
Response time (fast)	5 ms	Power consumption (typical) *	15 W
Pixel pitch	0.27 x 0.27 mm	Power consumption (standby) *	0.3 W
Pixel density	94 ppi	Power consumption (max)	205 W
Viewable size, horizontal	51.8 cm	Power consumption (off)	0.3 W
Viewable size, vertical	32.4 cm		

Display		Power	
Viewable size diagonal	61.1 cm	AC input voltage	100 - 240 V
Digital horizontal frequency	30 - 127 kHz	AC input frequency	50/60 Hz
Digital vertical frequency	48 - 100 Hz	Input current	2.5 A
Surface hardness	3H	Power supply type	Internal
Colour depth	8 bit	Energy efficiency scale	A to G
sRGB coverage (typical)	99%	Operational conditions	
Performance		Operating temperature (T-T)	0 - 40 °C
NVIDIA G-SYNC *	✗	Storage temperature (T-T)	-20 - 60 °C
AMD FreeSync *	✗	Operating relative humidity (H-H)	10 - 80%
Flicker-free technology	✓	Storage relative humidity (H-H)	5 - 90%
Low Blue Light technology	✓	Operating altitude	0 - 5000 m
Multimedia		Non-operating altitude	5000 - 12192 m
Built-in speaker(s) *	✗	Weight & dimensions	
Built-in camera *	✗	Width (with stand)	531.8 mm
Design		Depth (with stand)	181.8 mm
Market positioning *	Consumer	Height (with stand)	511.2 mm
Product colour *	Black	Weight (with stand)	4.95 kg
Ports & interfaces		Width (without stand)	531.8 mm
Built-in USB hub *	✓	Depth (without stand)	50 mm
USB upstream port type	USB Type-C	Height (without stand)	343.7 mm
Number of USB Type-C upstream ports quantity	1	Weight (without stand)	3.45 kg
USB Type-A downstream ports quantity	3	Bezel width (side)	6.7 mm
USB Type-C downstream ports quantity	1	Bezel width (top)	6.7 mm
USB Type-C DisplayPort Alternate Mode	✓	Bezel width (bottom)	1.3 cm
USB Power Delivery (USB PD)	✓	Packaging data	
USB Power Delivery up to	96 W	Package weight	7.03 kg
HDMI *	✓	Packaging content	
HDMI ports quantity	1	Stand included	✓
HDMI version	1.4	Cables included	Power, USB Type-C to USB Type-C
DisplayPorts quantity	1	Sustainability	
DisplayPort out quantity	1	Sustainability certificates	ENERGY STAR, TCO
DisplayPort out version	1.4	Doesn't contain	PVC/BFR, Arsenic, Mercury
Headphone out *	✗	Other features	
		Compliance certificates	RoHS



5397321029533

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.