



D-Link DGS-1210-52/ME Managed L2 Gigabit Ethernet (10/100/1000) 1U Black



Brand : D-Link

Product code: DGS-1210-52/ME/E

Product name : DGS-1210-52/ME

- 48 x 10/100/1000BASE-T ports
- 4 x SFP ports
- Comprehensive Layer-2 features including Link Aggregation, Port-based Q-in-Q, and VLAN trunking
- Enhanced network security with IP-MAC Port-Binding (IMPB), Access Control List (ACL), and IEEE 802.1X
- Embedded 6kV surge protection, sub-50ms recovery ERPS, and Dying Gasp provide optimal reliability
48 x 10/100/1000BASE-T, 4 x SFP ports, 104 Gbps, 440 x 210 x 44 mm
D-Link DGS-1210-52/ME. Switch type: Managed, Switch layer: L2. Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000), Basic switching RJ-45 Ethernet ports quantity: 48, Console port: RJ-45. MAC address table: 16000 entries, Switching capacity: 104 Gbit/s. Networking standards: IEEE 802.1D, IEEE 802.1Q, IEEE 802.1p, IEEE 802.1s, IEEE 802.1v, IEEE 802.1w, IEEE 802.1x, IEEE.... Rack mounting, Form factor: 1U

Management features		Protocols	
Switch type *	Managed	Supported network protocols	IPv4 / IPv6
Switch layer	L2	Design	
Quality of Service (QoS) support	✓	Rack mounting *	✓
Web-based management	✓	Form factor	1U
System event log	✓	Product colour	Black
MIB support	RFC1213 MIB II, RFC1493 Bridge MIB, RFC1907 SNMPv2 MIB, RFC1757, 2819 RMON MIB, RFC2021 RMONv2 MIB, RFC1398, 1643, 1650, 2358, 2665 Ether-like MIB, RFC2674, 4363 802.1p MIB, RFC 2233, 2863 IF MIB, RFC 2618 RADIUS Authentication Client MIB, RFC 2620 RADIUS Accounting Client MIB, RFC 2925 Ping & Traceroute MIB, Private MIB, D-Link Zone Defense MIB	LED indicators	Link, Status
		Number of fans	2 fan(s)
		Performance	
		Flash memory	16 MB
		Power	
		Power source *	AC
		AC input voltage	100 - 240 V
		Power over Ethernet (PoE)	
		Power over Ethernet (PoE) *	✗
Ports & interfaces		Operational conditions	
Basic switching RJ-45 Ethernet ports quantity *	48	Operating temperature (T-T)	-5 - 50 °C
Basic switching RJ-45 Ethernet ports type *	Gigabit Ethernet (10/100/1000)	Storage temperature (T-T)	-20 - 70 °C
SFP module slots quantity	4	Operating relative humidity (H-H)	0 - 95%
Console port	RJ-45	Storage relative humidity (H-H)	0 - 95%
Network		Weight & dimensions	
Networking standards *	IEEE 802.1D, IEEE 802.1Q, IEEE 802.1p, IEEE 802.1s, IEEE 802.1v, IEEE 802.1w, IEEE 802.1x, IEEE 802.3ah	Width	440 mm
		Depth	250 mm
		Height	44 mm
		Weight	3.96 kg
Port mirroring	✓		
Flow control support	✓		
Spanning tree protocol	✓		
VLAN support	✓		
Number of VLANs	4094		
Data transmission			
Switching capacity *	104 Gbit/s		
MAC address table *	16000 entries		
Packet buffer memory	1 MB		
Security			
IGMP snooping	✓		



0790069468223



790069468223

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.