



## Canon RF 200-800 mm F6.3-9 IS USM Telephoto Camera Lenses, Black/White



**Brand :** Canon

**Product code:** 6263C005

**Product name :** RF 200-800 mm F6.3-9 IS USM Telephoto Camera Lenses, Black/White

- A greater reach with flexibility and freedom
- Compact, weather resistant design
- Nano USM motor for smooth, fast and quiet autofocus
- High image quality and reduced chromatic aberration
- Easy control over camera settings or manual focus

RF 200-800 mm F6.3-9 IS USM Telephoto Camera Lenses, Black/White

Canon RF 200-800 mm F6.3-9 IS USM Telephoto Camera Lenses, Black/White. Component for: MILC, Lens structure (elements/groups): 17/11, Lens type: Telephoto zoom lens. Camera brands compatibility: Canon, AF actuator: USM, Lens colour: White. Product colour: Black, White, Mounting type: Bayonet. Country of origin: Japan, Quantity per pack: 1 pc(s), Layers per pallet: 2 pc(s). Diameter: 10.2 cm, Filter size: 95 mm, Length: 314.1 mm

| Lens system                                   |                                   | Performance                                  |              |
|-----------------------------------------------|-----------------------------------|----------------------------------------------|--------------|
| Component for *                               | MILC                              | Camera brands compatibility *                | Canon        |
| Lens type *                                   | Telephoto zoom lens               | Circular aperture                            | ✓            |
| Lens structure (elements/groups) *            | 17/11                             | Number of Ultra-low Dispersion (UD) elements | 3            |
| Lens viewing angle, horizontal                | 10° - 2° 35'                      | Lens hood                                    | ✓            |
| Focus adjustment                              | Auto/Manual                       | Lens hood model                              | ET-101       |
| Lens viewing angle, vertical                  | 7° - 1° 40'                       | <b>Design</b>                                |              |
| Lens viewing angle, diagonal                  | 12° - 3° 05'                      | Product colour                               | Black, White |
| Focal length range                            | 280 - 1120 mm                     | Mounting type                                | Bayonet      |
| Minimum aperture number *                     | 32                                | Dustproof                                    | ✓            |
| Number of diaphragm blades                    | 9                                 | Weatherproof                                 | ✓            |
| Closest focusing distance *                   | 0.8 m                             | <b>Logistics data</b>                        |              |
| Maximum aperture number *                     | 13                                | Country of origin                            | Japan        |
| Macro ratio                                   | 1:4                               | Quantity per pack                            | 1 pc(s)      |
| Zoom capability *                             | ✓                                 | Layers per pallet                            | 2 pc(s)      |
| Image sensor format                           | Full frame                        | Master (outer) cases per pallet layer        | 8 pc(s)      |
| Lens mount interface *                        | Canon RF                          | <b>Weight &amp; dimensions</b>               |              |
| Teleconverter/Extender compatible             | ✓                                 | Length                                       | 314.1 mm     |
| Control ring                                  | ✓                                 | Weight                                       | 2.05 kg      |
| Image stabilizer                              | ✓                                 | Diameter *                                   | 10.2 cm      |
| Image stabilizer type                         | Optical Image Stabilization (OIS) | Filter size *                                | 95 mm        |
| Image stabilizer number of stops              | 5.5                               | <b>Packaging data</b>                        |              |
| Image stabilizer number of stops (OIS)        | 5.5                               | Package width                                | 400 mm       |
| Image stabilizer number of stops (IBIS x OIS) | 5.5                               | Package depth                                | 450 mm       |
| <b>Performance</b>                            |                                   | Package height                               | 250 mm       |
| Auto focus                                    | ✓                                 | Package weight                               | 2.2 kg       |
| Manual focus                                  | ✓                                 | Package type                                 | Box          |
| AF actuator                                   | USM                               |                                              |              |
| Lens colour                                   | White                             |                                              |              |

#### Packaging content

|                        |      |
|------------------------|------|
| Lens cap included      | ✓    |
| Lens cap model         | E-95 |
| Rear lens cap included | ✓    |
| Rear lens cap model    | RF   |
| User guide             | ✓    |



4549292222050

### Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.