

ASUS ROG Loki SFX-L 850W Platinum White power supply unit 24-pin ATX


Brand : ASUS

Product family: ROG

Product code: 90YE00N2-B0NA00

Product name : Loki SFX-L
850W Platinum White

ROG Loki SFX-L 850W Platinum power supply (fully modular power supply, 80+ Platinum, Lambda A certified, 120mm PWM ARGB fan, Aura Sync RGB lighting, ATX 3.0 compatible, PCIe 5.0 ready, white) ASUS ROG Loki SFX-L 850W Platinum White. Total power: 850 W, AC input voltage: 100 - 240 V, Combined power (+3.3V): 110 W. Motherboard power connector: 24-pin ATX, Motherboard power cable length: 45 cm, SATA power cable length: 600 mm. Purpose: PC, Power supply unit (PSU) form factor: SFX-L, 80 PLUS certification: 80 PLUS Platinum. Product colour: White, Cooling type: Active, Fan diameter: 12 cm. Compliance certificates: RoHS



Power		Ports & interfaces	
Total power *	850 W	CPU power cable length	55 cm
AC input voltage *	100 - 240 V	Cabling type	Fully-Modular
Combined power (+3.3V)	110 W	Performance	
Combined power (+12V)	850 W	80 PLUS certification *	80 PLUS Platinum
Combined power (+5V)	110 W	Supported motherboard form factors	ATX
Combined power (-12V)	9.6 W	Purpose *	PC
Combined power (+5Vsb)	12.5 W	Power supply unit (PSU) form factor *	SFX-L
Max output current (+3.3V)	20 A	Bearing technology	Ball bearing
Max output current (+12V)	70.8 A	Design	
Max output current (+5V)	20 A	Product colour	White
Max output current (-12V)	0.8 A	Cooling type	Active
Max output current (+5Vsb)	2.5 A	Fan diameter	12 cm
Power protection features	Over power, Over voltage, Overcharge, Overheating, Short circuit, Under voltage	Number of fans	1 fan(s)
Ports & interfaces		Illumination	✓
Motherboard power connector *	24-pin ATX	On/off switch	✓
Motherboard power cable length	45 cm	Certificates	
Number of SATA power connectors	6	Compliance certificates	RoHS
SATA power cable length	600 mm	Weight & dimensions	
Peripheral (Molex) power connectors (4-pin) *	4	Width	125 mm
Peripheral (Molex) power cable length	600 mm	Depth	125 mm
PCI Express power connectors (8-pin)	3	Height	63.5 mm
PCI Express power connectors (16-pin)	1	Weight	1.81 kg
PCI Express power cable length	45 cm	Packaging data	
CPU power connector (4+4 pin)	✓	Package width	285 mm
		Package depth	190 mm
		Package height	100 mm
		Package weight	2.5 kg
		Package type	Box

Technical details

Sustainability compliance





4711081722229



0195553722223



195553722223

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.