

Vertiv Liebert GXT5 Double Online Conversion UPS - 1500VA/1500W| 230V| With Rackmount Kit| GXT5-1500IRT2UXL



Brand : Vertiv

Product family: Liebert

Product code:
GXT5-1500IRT2UXL

Product name : GXT5 Double
Online Conversion UPS -
1500VA/1500W| 230V| With
Rackmount Kit|
GXT5-1500IRT2UXL

- It offers reliable, easy-to-manage power protection and battery backup with 1500VA(1500W) capacity.
 - It has UNITY Power Factor (1.0) for more usable power and more connected loads to save space and costs.
 - It includes four individual programmable output receptacles for device control and optimum battery usage.
 - It comes with a Vertiv 3-year warranty plus a 2-year extension for a total of 5 years in coverage.
 - It is ENERGY STAR® 2.0 certified with higher efficiency, for energy savings and improved reliability.
- 2U Rack/Tower | 4 Hour Recharge | 5.60 Minute Stand-by | 230 V AC Input | 200 V AC, 208 V AC, 220 V AC Output | 8 x IEC 60320 C13 Receptacle(s) | Single Phase | Pure Sine Wave | Serial Port | Remote Monitoring | 5-year Warranty (3-year Standard Warranty + 2-year Extended Warranty)

Features		Battery	
UPS topology *	Double-conversion (Online)	Typical backup time at half load	16.3 min
Output power capacity *	1.5 kVA	Charging current	2.2 A
Output power *	1500 W	Design	
Waveform *	Pure sine	Form factor *	Tower
Input operation voltage (min) *	115 V	Rack capacity	2U
Input operation voltage (max) *	280 V	Product colour *	Black
Input frequency *	40 - 70 Hz	Display type	LCD
Output operation voltage (min)	200 V	Operational conditions	
Output operation voltage (max)	240 V	Operating temperature (T-T)	0 - 40 °C
Efficiency	93%	Storage temperature (T-T)	-20 - 60 °C
Power factor	0.99	Operating relative humidity (H-H)	0 - 95%
ECO mode	✓	Operating altitude	0 - 3000 m
Noise level	46 dB	Certificates	
Ports & interfaces		Certification	UL-1778 (Fifth Edition), C-UL listed, IEC 62040-1: 2008 (First Edition) + Am 1:2013, EN 62040-1:2008+A1:2013, CISPR22 Class A (RFI)/ FCC Part 15 (Class A), ISTA Procedure 1A, ANSI C62.41 Category B
AC outlet types	C13 coupler		
Power plug	C14 coupler		
AC outlets quantity	8 AC outlet(s)		
USB port	✓		
Serial interface	✓		
Serial interface type	RJ-45		
Modem (RJ-11) ports	1		
Ethernet LAN (RJ-45) ports	2	Weight & dimensions	
Battery		Width	430 mm
Typical backup time at full load	5.6 min	Depth	470 mm
		Height	85 mm
		Weight	21.4 kg
		Packaging data	
		Package width	617 mm
		Package depth	570 mm
		Package height	262 mm
		Package weight	25.9 kg



0767041026528



767041026528

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.